

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

RECEIVED

JUN 08 1983

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO RE-ENTER OR PLUG BACK TO A DIFFERENT USE. C-101 FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☐ OTHER- **X - Water Injection Well**

Name of Operator
Anadarko Production Company

Address of Operator
P. O. Drawer 130, Artesia, New Mexico 88210

Location of Well

UNIT LETTER **F** **2310** FEET FROM THE **North** LINE AND **2310** FEET FROM
THE **West** LINE, SECTION **9** TOWNSHIP **18S** RANGE **29E** NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3492' GL

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

7. Unit Agreement Name
Far West Loco Hills Sand Unit

8. Farm or Lease Name
Tract No. 9

9. Well No.
14

10. Field and Pool, or Wildcat
Loco Hills-Queen-Grayburg-San Andres

12. County
Eddy

6. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☒
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Rigged up pulling unit.
2. Circulated hole with mud consisting of 10# brine with salt gel.
3. 1st. Plug: 2452' - 2100' (100 sx); tagged plug @ 2155'.
4. Perforated 4 cement squeeze holes @ 825' (40' below salt section).
5. 2nd. Plug: 825' - 570' (45 sx); squeezed 20 sx out squeeze holes @ 600 psig; tagged plug @ 675'.
6. Perforated 4 cement squeeze holes @ 355' (17' above 8-5/8" casing shoe & 15' below top of salt section).
7. 3rd. Plug: 355' - 0' (110 sx). Circulated cement down 7" casing and up 8-5/8" casing annulus to surface.
8. Erected P & A marker, cleaned & leveled location & cut off tiedowns.

Note: Mud consisting of 10# brine with salt gel was used between all plugs.
Cement was Class H.

Post ID-2
6-17-83
P+H

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Larry Brooks* TITLE Area Supervisor DATE May 28, 1983

ORIGINAL SIGNED
BY LARRY BROOKS
GEOLOGIST - NMOCD

APPROVED BY _____ TITLE _____ DATE 7/18/83

CONDITIONS OF APPROVAL, IF ANY: