Form 3160-5 (August 1999)

Yates 3a. Address 105 S

N.M. Oil Cons. Division UNITED STATES

FORM APPROVED OMB No. 1004-0135

TC-054253

Expires November 30, 2000

01510

DEPARTMENT OF THE INTERIOR 11 S. 1st Street BUREAU OF LAND MANAGEMENTA TOSIA, NM 88210-283

Lease Serial No.

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.	6. If Indian, Allottee or Tribe Name		
SUBMIT IN TRIPLICATE - Other instructions on reverse side Control	7.—If Unit or CA/Agreement, Name and/or No.		
Type of Well	S/ Well Name and No.		
Oil Well Gas Well Other	1: 7		
Name of Operator	WLHU G4S Unit Tract 5-3		
Yates Petroleum Corporation	9. API Well No. 🗸		
Address 3b. Phone No. (include area code)	30-015-03366		
105 S. 4th St Artesia, NM 88210 505-748-1471	10. Field and Pool, or Exploratory Area		
Location of Well (Footage, Sec., T., R., M., or Survey Description)	Loco Hills-Queen-GB-SA		
	11. County or Parish, State		
330' FNL & 2310' FWL of Section 10-T18S-R29E (Unit C, NENW)	•		
	Eddy Co., NM		

12. CHECK AF	PPROPRIATE BOX(ES)	TO INDICATE NATU	RE OF NOTICE, REPORT,	OR OTHER DATA
TYPE OF SUBMISSION TYPE OF ACTION			PE OF ACTION	
	Acidize	Deepen	Production (Start/Resume)	Water Shut-Off
Notice of Intent	Alter Casing	Fracture Treat	Reclamation	■ Well Integrity
Cubanguant Banart	Casing Repair	New Construction	Recomplete	Other
_ Subsequent Report	Change Plans	X Plug and Abandon	Temporarily Abandon	
Final Abandonment Notice	Convert to Injection	Plug Back	☐ Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has * Set CIBP as close as possible to bottom of 7" casing, determined that the site is ready for final inspection.)

Propose to plug and abandon as follows:

TOOH with 2-7/8" tubing. 1.

- TIH with wireline set CIBP and set CIBP at 2428'. TOOH. TIH with tubing & tag CIBP. Load hole with plugging mud. Keep wellbore loaded with plugging mud.
- 3. Spot a 30 sack Class C cement plug from 2428-2293'. TOOH with tubing.
- Perforate 7" casing with 6 holes at 1100' and 6 holes at 473'. 340
- TIH with wireline set cement retainer and set retainer at 1050'. TOOH. tubing. If necessary, load hole with plugging mud. Sting into retainer and establish injection rate. Squeeze with 75 sacks Class C cement. Leave 35' of cement on top of retainer. TOOH with tubing.
- Nipple down BOP. TIH with wireline set cement retainer and set retainer at 373'. TOOH. TIH with tubing. If necessary, load hole with plugging mud. Sting into retainer and establish circulation. Squeeze with 60 sacks Class C cement from 473-373'. Leave

	35' of cement on top of retainer. TOOH with	<u>tubi</u>	ng.
4.	I hereby certify that the foregoing is true and correct Name (Printed/Typed)	C	CONTINUED ON NEXT PAGE:
	Rusty Klein	Title	Operations Technician
	Signature August Signature	Date	March 14, 2000

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

(ORIG. SGD.) ALEXIS C. SWOBODA

PETROLEUM ENGINEER

MAR 17 2000

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willful States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

RECEIVED

MAR 16 2000

BLM ROSWELL, NM YATES PETROLEUM CORPORATION WLHU G4S Unit Tract 5-3 Section 10-T18S-R29E Eddy County, New Mexico

SUNDRY NOTICE CONTINUED:

- 7. Spot a 15 sack Class C cement plug at surface.
- 8. Install regulation abandonment marker.

NOTIFY BLM-CARLSBAD (505-887-6544) AND OCD-ARTESIA (505-748-1283) 24 HOURS PRIOR TO COMMENCING PLUGGING OPERATIONS

Rusty Klein

Operations Technician

March 14, 2000

CATION:3		7-85-77E Eddy run	ty
.: 3500' ZERO: _	' AGL:'	CASING PROGRA	4.
	RLG./COMPL. DATE:	STZEZWY./GR./CUMM.	DEPTH SE
PHENTS:	Soud: 4-10-47 Compl: 5-22-47		
		Q × g li	423
		<i>5" 20</i> ₩	250
{, 			
{'	y toc?		
{ ',	1/2		
 		<u> </u>	
3/1	859" @ 423'		
7	W/30 sx		
 			
{ }			
()			
\	:		
5 1	} {		
} [1 (
)			
1) (2==20=	
{'/	1) Toc?	BEFORE	
} ()	1/		
{ /	(1)		
1	[./}		
[/]	',}		
17			
[1]	17/		
1.1			
	17)		
[7]			
1			
1./1	/		
	7" e 2503'	•	•
}	w/100 sx		•
}	\		
}	(
l	v -)		
}	Dil Zone 1591-	26/7' Tops:	Salt 4/0
j	Gas @ 2607'		Anhydrite 875 Red Sand 209
}	1		Red Sand 209
)			
}	1		
()		
l	1		

WELL HAHE:	NIHIT.	5-3	FIELD AREA:		
LOCATION:	330'FUL	10' FWL 10-	185-27E Fdd	y cunty	
GL: <u>35CO</u>	ZERO:'AGL: ORIG. DRLG./COMPL. I	 DATE:	CASI	NG PROGRAM:	
COMMENTS:	Shud: 4	- 10 - 47	STZE/WT./GH./CUM.		DEPTII SET
	Compl: 5	- 22 - 47	Q ×g"		4237
			7" 20#		2505
<u>[₹</u>	四至 1000000000000000000000000000000000000	15 sx to Surface			
{	'/ 	toc?			
}	\\ \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	mt Retainer @ 373 with 35°Cmt			
}					••
٤		858" @ 423' w/30 sx			
		W/30 3x			
	P.	.fe 473' Sgz	W/60sx cmt,	1173 - 373	
		•	- C - C - C - C - C - C - C - C - C - C	4/3 0/0	
	}				
			- 1 ·		
	(mt Retairer @ 10.			
	Por	fe 1100' Sqz u	1/75'sk		
	-{{ - 3} - '	oc?			
	{		H	FTER	
	37 3		•		
	十月 13				
	17 17				
	1.1 1.1	•	0.n'		
	1/955/1	30 5x 2428- 6	, 293		
		CIBL 6 2418			
	7"				
		@ 2503' w/100 sx			
	}	•			
	1				
	1 0	il Zone 1591	26/7'	Tops: Salt	4/0'
	1	ias @ 2607'		Inhyd	tite 875'
	}			Red S	and 1045
	(
	TD 2619'				