

N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

AREA 640 ACRES
LOCATE WELL CORRECTLY

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

R. V. Fair
Company or Operator
Trainerd
Well No. 6 in 00 00 of Sec. 10 T. 18
Lease
R. 29 N. M. P. M. Loco Hills Field, Eddy County.
Well is 990 feet north of the North line and 330 feet south of the East line of Section 10
If State land the oil and gas lease is No. Assignment No.
If patented land the owner is Address
If Government land the permittee is Julia Trainerd Address Artesia, New Mexico
The Lessee is R. V. Fair Address Artesia, New Mexico
Drilling commenced 1-28-40 19 Drilling was completed 3-7-40 19
Name of drilling contractor Dodson Drilling Co. Address Artesia, New Mexico
Elevation above sea level at top of casing feet.
The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from none to No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.
No. 1, from 205 to 272 feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
8 1/2"	26#	3		420'	Plain				
7" OD	20#	3		2523'	Plain				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
10"	8 1/2"	420'	50	Halliburton		
8"	7" OD	2523'	100	Halliburton	Heavy	Circulated

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
	1 1/2"	Nitro	1300 lbs	3-13	2570-2610	

Results of shooting or chemical treatment After shot, gas increased from approximately 3,000,000 cu. ft. to an estimated 4,000,000 cu. ft. Did not produce oil.

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet
Cable tools were used from 0 feet to 2730 feet, and from feet to feet

PRODUCTION

Put to producing 19
The production of the first 24 hours was barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Ba
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

Glenn Hill Driller Perry Triplett Driller
O. E. Wood Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 5th day of April, 1940
Notary Public
My Commission expires 2-28-44
Artesia, New Mexico April 5, 1940
Place Date
Name Frank P. Collins
Position Bookkeeper
Representing R. V. Fair
Company or Operator
Address Box 516, Artesia, New Mexico

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	10		Surface sand
10	30		Caliche
30	50		Red sand
50	75		Clumbo
75	120		Sand and red rock
120	130		Red shale
130	135		Gravel
135	275		Anhy
275	372		Water sand
372	380		Red rock
380	385		Red sand
385	398		Anhy and shale
398	400		Salt and anhy
400	410		Anhy
410	415		Red sand
415	435		Anhy
435	438		Lime and anhy
438	440		Anhy
440	450		Sand
450	452		Anhy
452	455		Lime
455	460		Anhy
460	465		Lime
465	469		Gas sand
469	475		Lime
475			Total depth