

NO. OF COPIES RECEIVED	6
DISTRIBUTION	
SANTA FE	1
FILE	1-
U.S.G.S.	
LAND OFFICE	
OPERATOR	4

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>	
1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- WIW	7. Unit Agreement Name WEST LOCO HILLS UNIT
2. Name of Operator NEWMONT OIL COMPANY	8. Farm or Lease Name Tract 37
3. Address of Operator ROOM 303 FIRST NATIONAL BANK BLDG., ARTESIA, NEW MEXICO	9. Well No. 2
4. Location of Well UNIT LETTER A , 330 FEET FROM THE North LINE AND 990 FEET FROM THE East LINE, SECTION 11 TOWNSHIP 18S RANGE 29E NMPM.	10. Field and Pool, or Wildcat Loco Hills
15. Elevation (Show whether DF, RT, GR, etc.) 3538	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
-------------------------	-----------------------

PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOBS <input type="checkbox"/> OTHER <input type="checkbox"/> Shut off thief zone	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/>
---	--	---	---

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4-9-65 Set cast iron bridge plug at 2577 and pump in 50 sks Class "C" cement followed by 50 sks Class "C" cement with 200# walnut hulls

4-10-65 WOC

4/12/65 Drill out cement and test 1500# for 20 Mins. held okay

4/16/65 Clean out to 2697' and acidize with 500 gals reg. acid.

4/18/65 Return well to injection. Injection for first five days averaged 400 bbls at 1350 psi

RECEIVED

MAY 6 1965

O. C. C.
ARTESIA, OFFICE

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

ORIGINAL SIGNED BY
H. J. LEDBETTER

SIGNED _____ TITLE **Division Superintendent** DATE **4/28/65**

APPROVED BY *ML Armstrong* TITLE **Gen. Mgr. New Mexico** DATE **MAY 11 1965**

CONDITIONS OF APPROVAL, IF ANY: