


NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELL



HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

| | | | |
|--|-------------------------------------|--|--|
| REPORT ON BEGINNING DRILLING OPERATIONS | | REPORT ON REPAIRING WELL | |
| REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL | | REPORT ON PULLING OR OTHERWISE ALTERING CASING | |
| REPORT ON RESULT OF TEST OF CASING SHUT-OFF | <input checked="" type="checkbox"/> | REPORT ON DEEPENING WELL | |
| REPORT ON RESULT OF PLUGGING OF WELL | | | |

Artesia, New Mexico

Place

May 13, 1940

Date

OIL CONSERVATION COMMISSION
Santa Fe, New Mexico.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the.....

Martin Yates III (Bassett & Birney et al) Well No. 6 in the

Company or Operator

Lease

M. J. Sel

of Sec. 11

T. 18 S.

R. 29 E.

N. M. P. M.,

Loxo Hills

Field,

Eddy

County

The dates of this work were as follows: May 7th to 9th, 1940

Notice of intention to do the work was (void) submitted on Form C-102 on May 7, 1940 19
and approval of the proposed plan was (void) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On May 7, 1940, set 435 ft. of 8 $\frac{1}{2}$ " salt string approximately 21 ft. below the top of salt with the Halliburton process, cementing with 50 sacks of cement. Permitted the cement to set for 72 hours in order to test cement and water shut-off, then bailed the hole dry. Drilled cement plug and bailed hole dry again and let set for one hour before testing water shut-off. Result -- complete water shut-off. Resumed drilling operations.

Witnessed by Martin Yates III (Bassett & Birney et al)
Name Company Title

Subscribed and sworn to before me this 14th

day of May, 1940

Laura Bullock
Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name Lorene Jones

Position Agent

Representing Martin Yates, III (Bassett & Birney
Company or Operator Birney

My Commission expires Dec. 6, 1945

Address Box 434, Artesia, N. Mex. at al)

Remarks:

Roy Jacobrogh
Oil & Gas Inspector

Title