

RECEIVED BY

MAR 20 1985

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYNM OIL CONS. COMMISSION
SUBMIT IN THE
Dr. [unclear] Instructions on Form
Artesia, NM 88210Form approved.
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

LC-060904

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

West Loco Hills Grb #4 Sd

8. FARM OR LEASE NAME

TRACT 13

Ut

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Loco Hills (O.G.Sa)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 12-18-29

12. COUNTY OR PARISH

13. STATE

Eddy

OIL ☐ GAS ☐ OTHER ☐

WIW - TA

2. NAME OF OPERATOR

YATES Petroleum Corp
NEWMONT OIL COMPANY

3. ADDRESS OF OPERATOR

P. O. BOX 1305, ARTESIA, NEW MEXICO 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

330 FNL 330 FEL Sec. 12-18-29

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3543'

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) P&AREPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

7/13/83...Tagged bottom. Spotted 100 sks cement w/2% Calcium. WOC. Tagged plug at 2587'. Pressured up to 500 psi at 820'. Held. Perf 4 shots/ft. @ 1170'. Squeezed 50 sks cmt w/2% Calcium. SI 200 psi. WOC.

7/14/83...Pressured to 500 psi. Held. Tagged plug at 1040'. Perf. 4 shots at 390'. Spotted 50 sks cmt w/2% Calcium. Bullhead squeezed w/200 psi. WOC. Tagged plug at 273'. Pressure tested plug to 400 psi. Mixed 15 sks cmt for top hole plug. Installed P&A marker.

Cleaned location, seeded and ready for inspection.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Area Manager

DATE 9/14/83

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side