Form 9-331 Dec. 1973 UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	CONSISTION Form Approved. Budget Bureau No. 42-R1424 COSTO 5. LEASE LC 063808 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deeden or plug back to a different reservoir. Use Form 9-331-C for such proposals.) 1. oil gas well other 2. NAME OF OPERATOR Anadarko Production Company V 3. ADDRESS OF OPERATOR P. O. Drawer 130, Artesia, New MARIESA 895510F	10. FIELD OR WILDCAT NAME Loco Hills-Queen-Grayburg-San Andres 11. SEC., T., R., M., OR BLK. AND SURVEY OR
<ul> <li>4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)</li> <li>AT SURFACE: 330' FN &amp; ELS Sec. 18,T18S,R29E</li> <li>AT TOP PROD. INTERVAL: Same</li> <li>AT TOTAL DEPTH: Same</li> </ul>	AREA       18 - 18S - 29E         12. COUNTY OR PARISH       13. STATE         Eddy       New Mexico         14. API NO.       14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA         REQUEST FOR APPROVAL TO:       SUBSEQUENT REPORT OF:         TEST WATER SHUT-OFF	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3555 Report results of multiple completion or zone chaptern 2007 4999 ENL ( ) MINERALS REATE, SERVICE ROSWELL, NEW MEXICO
<ol> <li>DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertiner</li> <li>Rig up pulling unit.</li> <li>Trip out of hole with rods and tubing.</li> <li>Rig up reverse unit; clean out to 2750 with</li> <li>Run a slotted 5½" liner from 2750' to 2150"</li> <li>Q 2750' with top of liner at 2150'.</li> <li>Re-run tubing and rods and return to pump.</li> </ol>	h 62" bit.

Subsurface Safety Valve: Manu. and Type	Set @	Ft
18. I hereby ceptify that the foregoing is true and correct		
SIGNED SIGNED ATE Area Supervisor DATE	April 22, 1	983
APPROVED TITLE DATE DATE DATE		
DEPROVED BT'S. Sgd.) FETER W. CHESTER		
MAY 4 1983		

.

\*See Instructions on Reverse Side

.