

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐

2. NAME OF OPERATOR  
**Anadarko Production Company**

3. ADDRESS OF OPERATOR  
**P. O. Drawer 130, Artesia, New Mexico 88210**

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: **330' FN & ELs Sec. 18, T18S, R29E**  
AT TOP PROD. INTERVAL: **Same**  
AT TOTAL DEPTH: **Same**

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☒ **Install liner**

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

5. LEASE  
**LC 063808**

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME  
**Ballard Grayburg San Andres Unit**

8. FARM OR LEASE NAME  
**Tract No. 16-A**

9. WELL NO.  
**1**

10. FIELD OR WILDCAT NAME  
**Loco Hills-Queen-Grayburg-San Andres**

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
**18 - 18S - 29E**

12. COUNTY OR PARISH **Eddy** 13. STATE **New Mexico**

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
**3555'**

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

MAY 5 1983

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1. Rigged up pulling unit.
2. Tripped out of hole with rods and tubing.
3. Rigged up reverse unit; cleaned out to 2833' with 6 1/4" bit.
4. Ran a slotted 5 1/2" liner from 2833' to 2137'. The bottom of this uncemented liner is on PBTD of 2833' with top of liner at 2137'.
5. Re-ran tubing, rods and bottom hole pump. Tubing @ 2736' SNOE. Returned well to pump.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED David R. Glass TITLE **Area Supervisor** DATE **May 4, 1983**

ACCEPTED FOR RECORD  
(ORIG. SGD.) **DAVID R. GLASS**

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL **SEP 06 1983**

ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side