

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other ☐ P&A

2. NAME OF OPERATOR

Yates Drilling Co. *Yates Drilling Co.*

3. ADDRESS OF OPERATOR

207 S. 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1650 FSL & 715 FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE

NM 026492

expired

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

(Sims & Reese) Pure Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Loco Hills Q-G-SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit L, Sec. 19-T18S-R29E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Replug Well. ☐

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

RECEIVED

SEP 13 1982

Report results of multiple completion or zone change on Form 9-331-C 1 1982

O. C. D.

ARTESIA, OFFICE

RECEIVED

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSEMILL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

NMOCD Order No. R-7012 requires well to be replugged before commencement of injection of water in Phase I injection wells for South Loco Hills (Grayburg) Unit.

5-1/2" casing at 2350' w/100 sxs. Perforations at 2304-46'. 15 sx plug over perms #2100' plug 700-800' #300' plug 274-375', 5-1/2" casing stub at 1619'. Propose to re-enter, drill out existing plugs down to 2304'. Plug Grayburg-Dolomite w/50 sxs #100 sxs in and out of 5-1/2" stub, 25 sxs at base of Salt, 25 sxs at top of Salt, 10 sx surface plug.

Iron c 1790

Stub 1607

#1 Plug 1790-1550

#2 Plug 780-680

#3 Plug 335-225

#4 Surface

Set @ _____ Ft.

Subsurface Safety Valve: Manu. and Type _____

18. I hereby certify that the foregoing is true and correct

SIGNED *Peter W. Chester*

TITLE Engineering Secty

DATE 9-7-82

APPROVED (This space for Federal or State office use)
APPROVED BY *Sgt. PETER W. CHESTER*
CONDITIONS OF APPROVAL, IF ANY:

APPROVED

SEP 10 1982

FOR

JAMES A. GILLHAM
DISTRICT SUPERVISOR

*See Instructions on Reverse Side