

30-015-03443

10/26/62

Lane Hills

Gemma Lay/

Neutron

UNITED STATES, NM 88210  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☐ P&A

2. NAME OF OPERATOR  
Yates Drilling Co.

3. ADDRESS OF OPERATOR  
207 S. 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1650 FSL & 715 FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>

(other) Replug well. NMOCD Order No. R-7012

5. LEASE  
NMOCD Order (expired)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
(Sims & Reese) Pure Federal

9. WELL NO. 1

10. FIELD OR WILDCAT NAME  
Loco Hills Q-G-SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Unit L, Sec. 19-T18S-R29E

12. COUNTY OR PARISH Eddy 13. STATE NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Replugged well as follows: Cleaned out to 1607'. Tagged old 5½" casing at 1607' w/7-7/8" bit. Ran 4-3/4" bit and cleaned out to 1790' inside old 5½" casing. Found metal or junk iron at this point. Set 100 sx Class "C" cement plug at 1790'. Tagged plug at 1590'. Mudded hole. Set 60 sx Class "C" cement w/2% CaCl plug at 780'. Tagged plug at 590'. Set 60 sx Class "C" w/2% CaCl plug at 325-200'. Used 50 sx Class "C" to fill large hole at surface. Set dry hole marker.

Work started September 23, 1982. Work completed September 29, 1982.

Witnessed by: Mr. Weaver, NMOCD, Artesia

Witnessed by: Mr. Jones, MMS, Artesia

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Leanda J. Ladd TITLE Engineering Secty DATE 10-18-82

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE 12/24/90  
CONDITIONS OF APPROVAL, IF ANY:

Approved as to plugging of the well bore.  
Liability under bond is retained until  
surface restoration is completed.

\*See Instructions on Reverse Side