

36-015-13478

11/2/84
under 4' + 1'

1-20-84
R.Y.

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☐ well other ☒ Injection Well
2. NAME OF OPERATOR
Yates Drilling Co.
3. ADDRESS OF OPERATOR
207 So. 4th St., Artesia, NM 88210
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660 FNL & 1980 FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

- TEST WATER SHUT-OFF ☐
- FRACTURE TREAT ☐
- SHOOT OR ACIDIZE ☐
- REPAIR WELL ☐
- PULL OR ALTER CASING ☐
- MULTIPLE COMPLETE ☐
- CHANGE ZONES ☐
- ABANDON* ☐
- (other) Convert to injection well.

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

DEC 8 1982

OIL & GAS

MINERALS MGMT. SERVICE

DOSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

October 22, 1982 - Rigged up and cleaned out sand w/sand pump.
October 25, 1982 - Ran casing scraper. Set packer at 2370'. Acidized w/1000 gallons 15% acid. Ran plastic lined packer and 2-3/8 plastic lined tubing. Set packer at 2316'. Loaded backside with treated water. (Top perms at 2414').

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Peter W. Chester TITLE Supervisor DATE 12-6-82

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY (Orig. Sgd.) PETER W. CHESTER
CONDITIONS OF APPROVAL JAN 4 1983

TITLE DATE
SIGNED TO LIKE
STATE

MINERALS MANAGEMENT SERVICE
DOSWELL, NEW MEXICO

*See Instructions on Reverse Side