

RECEIVED BY

NOV 7 1985

O. C. D.

## ARTESIA, SUNDY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

## 2. NAME OF OPERATOR

Yates Drilling Company

## 3. ADDRESS OF OPERATOR

207 South 4th Street, Artesia, N.M. 88210

## 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FNL &amp; 660' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

## 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON\* ☒(other) ☐

SUBSEQUENT REPORT OF

(NOTE: Report results of multiple completions or zone change on Form 9-130.)

## 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Production has dropped below economic limit.

We request approval to plug, as follows:

2012-1912'  
 Set 100 ft. plug ~~2012-1912'~~ in 4 1/2" prod. csg. across perfs. - *Tag*  
 Perforate 4 holes @ 850' and set 50' plug below retainer in and out of 4 1/2" csg. *Set C.R. at 800' - circ 4 1/2-7" annulus.*  
 Perforate 4 holes @ 850' and set 50' plug below retainer in and out of 4 1/2" csg. *Set 50' cnt. on top of C.R.*  
 Set marker in 5 sxs. @ surface.

Heavy mud will be placed between plugs.

*Set 100' plug at 401' (7" shoe)*  
 Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

## 18. I hereby certify that the foregoing is true and correct

SIGNED

*Joly Rhoden*

TITLE Engineer

DATE

8-5-85

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY

TITLE

DATE

11-5-85