N.M. Oil Cons Division

811 S. 1st Streut

FORM APPROVED

Form 3160-3
(June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR Artesia, NM 88210-

Budget Bureau No. 1004-0135 2834 Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS  Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  Use "APPLICATION FOR PERMIT-" for such proposals	LC-067348 6. If Indian, Allottee or Tribe Name	
SUBMIT IN TRIPLICATE	7. If Unit or CA, Agreement Designation	
Type of Well  Oil Gas Well Well Other	8. Well Name and No.	

332m. m 2.0		
I. Type of Well Oil Gas Well Other		8. Well Name and No.
2. Name of Operator Vintage Drilling LLC		Federal DY #2  9. API Well No.
3. Address and Telephone No. P.O. Box 158, Loco Hills NM 88255 505-748-2941	oca <sup>REC</sup> LIVEU	30-015-03525  10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T. R. M. or Survey Description) S-28, T-18S, R-29E	ARTESIA	Turkey Track, 7RVS, QN, G, SA
1650' FNL, 2310' FEL		Eddy, NM

12	CHECK APPROPRIATE BOX(s)	TO INDICATE NATURE OF NOTICE, RE	EPORT, OR OTHER DATA	
	TYPE OF SUBMISSION	TYPE OF AC	TYPE OF ACTION	
	Notice of Intent	Abandonment	Change of Plans	
	Subsequent Report	Recompletion Plugging Back	New Construction Non-Routine Fracturing	
	Final Abandonment Notice	Casing Repair Altering Casing	Water Shut-Off Conversion to Injection	
		Other	Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report rind Log form)	

13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Set cast iron bridge plug at 1950', cap with a minimum of 35' of cement.

Perforate at 1350', squeeze at least 100' of cement outside pipe, leave 100' of cement inside pipe. Tag
Perforate at 480', squeeze a minimum of 100' of cement in annulus, leave 100' cement in side pipe. Tag Set 50' cement plug at surface.

Will tag cement after each squeeze.

Date _	2/27/01
Date _	MAR 0 6 2001
-	

knowingly and willfully to make to any department or agency of the United States any false. fictitious or fraudulent statements

RECEIVED ROSWED

: