

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)Form approved. *SF file*
Budget Bureau No. 42 B1424

5. LEASE DESIGNATION AND SERIAL NO.

LC-067348

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Yates Drilling Company ✓		8. FARM OR LEASE NAME Federal Dy
3. ADDRESS OF OPERATOR 207 South 4th St., Artesia, NM 88210		9. WELL NO. 3
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FNL & 1980' FEL		10. FIELD AND POOL, OR WILDCAT Turkey Tract
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Unit B Section 28-18S-29E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3461' GR		12. COUNTY OR PARISH Eddy
		13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☒
☐
☐

REPAIRING WELL

☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

December 1, 1980 - We plugged back with frac sand above existing perfs 1910-14'; 1802-10 Perforated 4 holes @ 1550'. Set cement retainer @1512'. Squeezed w/100 sacks Halliburton Lite, 350 sacks Class C cement. We did not circulate cement to surface.

December 4, 1980 - Ran temperature survey - found top of cement @750', shot 4 holes @700'. Squeezed w/300 sacks Halliburton Lite w/15 lbs salt to sack & 100 sacks Class C 2% CaCl. Cement circulated 75 sacks Halliburton Lite to pit. We propose to temporarily abandon well for further evaluation.

Witnessed by Mr. Weaver, Oil Conservation Division, Artesia.

RECEIVED

DEC 11 1980

O. C. D.

ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Drilling Supervisor

DATE Dec. 8, 1980

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side