CHARLESTON UN STATES	5. Li
tesia, NM 88210 DEPARTMENT OF THE INTERIOR	LC-067348
stesia, NM 88210 GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
RECEIVED BY GEOLOGICAL SURVEY	O. II INDION, ALCO I LEE UK TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS NOV. Do dot use this form for proposals to drill or to deepen or plug back to a different reservoir, use Form 9-381-C for such proposals.)	7. UNIT AGRELMENT NAME
O. C. D.	8. FARM OR LEASE NAME Federal DY
ARTESIAN OF OPERATOR	9. WELL NO.
Yates Drilling Company 3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME Turkey Tracts - SA
207 South 4th Street, Artesia, N.M. 4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
below.)	Section 28-18S-29E
AT SURFACE: 660' FNL & 1980'FEL AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	12. COUNTY OR PARISH 13. STATE Eddy N.M.
	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF	3452'
TEST WATER SHUT-OFF THE TRACTURE TREAT	
SHOOT OR ACIDIZE	
REPAIR WELL [] [] [] [] PULL OR ALTER CASING []	tNOTE: Report results of multiple completion or zone change on Form 9-330.)
MULTIPLE COMPLETE	/ change on Form 3-330.)
ABANDON• [X] Revised []	, /
(other)	v.*
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is different measured and true vertical depths for all markers and zones pertined	firectionally drilled, give subsurface locations and
This well is temporarily abandoned. Cement b	behind the 45" csg. has been
circulated to the surface. The 4½" csg. has	the following plugs:
₹2045'-2010' cement	
1980'-1937' cement on top of cast iron	n bridge plug.
1980'-1937' cement on top of cast from 1937'-1732' frac. sand 1550'-1512' cement Retainer @ 1512'	
1550'-1512' cement Retainer 0 1512'	
Retainer @ 1512' 750 -650' cement with retainer at 650'	(4/2-7" annulus civen
We request permission to place marker at surf	face and abandon as is.
set de surface plug.	•
Subsurface Safety Valve: Manu, and Type	Set @ Ft.
18. I hereby certify that the Joyegoing is true and correct	
SIGNED John Kool TITLE Engineer	DATE 10-31-85
(This space for federal or State of	lice use)
APPROVED BY TIFLE CONDITIONS OF APPROVAL, IF ANY:	DATE 11-5-85