

RECEIVED BY

NOV 7 1985

O. C. D.

ARTESIA,

UNITED STATES

DEPARTMENT OF THE INTERIOR. COMMISSION

GEOLOGICAL SURVEY DD
Artesia, NM 88210

Budget Bureau No. 42-R1424

c/sf

SUNDY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other

2. NAME OF OPERATOR

Yates Drilling Company ✓

3. ADDRESS OF OPERATOR

207 South 4th Street, Artesia, N.M. 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1650' FSL & 990' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON*

(other)

SUBSEQUENT REPORT OF

5. LEASE

LC-067348

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal DY

9. WELL NO.

4

10. FIELD OR WILDCAT NAME

Turkey Track ~~SR-Q-G-SA~~

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

28-18S-29E

12. COUNTY OR PARISH 13. STATE

Eddy

N.M.

14. API NO.

15. ELEVATIONS (SHOW DE, KDB, AND WD)

3435' GR 3435' DE

(NOTE: Report results of multiple completion or zone change on Form 9-331-C)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Production has dropped below economic limit.

We request permission to plug, as follows:

Set a 100 foot plug from 2011' to 1911' in 4½" csg., across perfs. - Tag

Perforate 4 holes @ 850' and set 50 sack plug below retainer in 4½" csg.

Perforate 4 holes @ 320' and set 50 sack plug below retainer in 4½" csg.

Set marker in 5 sacks at surface.

Heavy mud will be placed between plugs.

① Set retainer at 800'. Circulate 4½-7" annulus
Set 50' cmt. on top of retainer.
Set 100' plug at 277' (7" csg shoe).

Subsurface Safety Valve: Manu. and Type

Set @

Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Toby Rhoder

TITLE Engineer

DATE

8-5-85

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

11-5-85

CONDITIONS OF APPROVAL, IF ANY

*See Instructions on Reverse Side

Post ID-2
11-22-85
YKA