



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office \_\_\_\_\_

Lease No. LC 062027

Unit 1

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

**Water Injection**  
**Brinard**

**January 3,** 1962

Well No. 6-10 is located 1325 ft. from ~~XX~~S line and 2645 ft. from ~~XX~~W line of sec. 34

N 1/4 of SE 1/4 34

185

29E

NMP

(1/4 Sec. and Sec. No.)

(Twp.)

(Range)

(Meridian)

**Turkey Track**

**Eddy**

**New Mexico**

(Field)

(County or Subdivision)

(State or Territory)

The elevation of the derrick floor above sea level is 3428 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Surface pipe: 370 feet of 8 5/8", new. Cemented with 100 sacks of Class A with 2% Ca Cl<sub>2</sub>.  
WOC 24 hours then pressure tested at 500 psig. 2148 feet of 4 1/2" pipe set  
and cemented with 130 sacks of 50-50 Litpar Cement.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Stanton Oil Company, Ltd.

Agent for R.E. McKee

Address 408 Wilkinson-Foster Building

Midland, Texas

By Original Signed by Wm. E. Fickert

Title Agent