Form C-102

NEW MEXICO OIL CONSERVATION COMMISSION

... ...

Santa, Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications con-sidered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking belew:	
NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING
NOTICE OF INTENTION TO REPAIR WELL	Notice of intention to use well as input w
NOTICE OF INTENTION TO DEEPEN WELL	Notice of intention to use well as input we the second sec
Artesia, New	Mexico January 25, 1945
	Place Date
DIL CONSERVATION COMMISSION, Santa Fe, New Mexico.	
Gentlemen:	
Following is a notice of intention to do certain work as d Franklin Patroleum Corp.	escribed below at the
f Sec. 5 T. 18S , R. 30E	, N. M. P. M., Loco Hills Field,
Eddy	
FULL DETAILS OF PRO	OPOSED PLAN OF WORK S AND REGULATIONS OF THE COMMISSION
Total depth 2885 011 Sands, from 2880 ' to 2885 Plugged back to'. Shet with 20 guarts nitro glyceria	
011 Sands, from 2880 ' to 2885 Plugged back to'. Shet with 20quarts mitro glycerin Cleaned out to 2885 '. Tubing 2849'-1". Packer-depth 2752'2". The input wells for this project were to Hills operators and were selected for Retablishing a uniform spacing of input s evenly throughout the field. Selecting input wells that are in a pro Selecting input wells that have other p	<pre>'&' to'. selected by the Engineering Committee of the the following reasons: wells in an effort to distribute the injecte per mechanical condition. producing wells on the same basic lease that ly assigned to the input well.</pre>
011 Sands, from 2880 ' to 2885 Plugged back to'. Shet with 20quarts nitro glycerin Cleaned out to 2885'. Tubing 2849'-1". Packer-depth 2752'2". The input wells for this project were to Hills operators and were selected for Establishing a uniform spacing of input s evenly throughout the field. Selecting input wells that are in a pro Selecting input wells that have other p n make up the allowable production normal Endeavoring wherever possible to limit	<pre>'&' to'. selected by the Engineering Committee of the the following reasons: wells in an effort to distribute the injecte per mechanical condition. producing wells on the same basic lease that ly assigned to the input well. individual companies to one input well in ord</pre>
011 Sands, from 2880 ' to 2885 Plugged back to'. Shet with <u>20</u> quarts mitro glycerin Cleaned out to <u>2885</u> '. Tubing <u>2849'-1".</u> Packer-depth <u>2752'2"</u> . The input wells for this project were to Hills operators and were selected for Establishing a uniform spacing of input s evenly throughout the field. Selecting input wells that are in a pro Selecting input wells that have other p make up the allowable production normal Endeavoring wherever possible to limit	<pre>'&' to'. selected by the Engineering Committee of the the following reasons: wells in an effort to distribute the injecte per mechanical condition. producing wells on the same basic lease that ly assigned to the input well. individual companies to one input well in ord company.</pre>
011 Sands, from 2880 ' to 2885 Plugged back to'. Shet with 20quarts mitro glycerim Cleaned out to 2885'. Tubing 2849'-1". Packer-depth 2752'2". The input wells for this project were to Hills operators and were selected for Establishing a uniform spacing of input s evenly throughout the field. Selecting input wells that are in a pro Selecting input wells that have other p n make up the allowable production normal Endeavoring wherever possible to limit t to place such a burden on an individual Approved	<pre>'&' to'. selected by the Engineering Committee of the the following reasons: wells in an effort to distribute the injecte per mechanical condition. producing wells on the same basic lease that ly assigned to the input well. individual companies to one input well in ord company. Franklin Petroleum Corporation By</pre>
011 Sands, from 2880 ' to 2885 Plugged back to'. Shet with <u>20</u> quarts mitro glycerin Cleaned out to <u>2885</u> '. Tubing <u>2849'-1".</u> Packer-depth <u>2752'2"</u> . The input wells for this project were to Hills operators and were selected for Retablishing a uniform spacing of input s evenly throughout the field. Selecting input wells that are in a pro Selecting input wells that have other p n make up the allowable production normal Rudeavoring wherever possible to limit t to place such a burden on an individual Approved	<pre> '&' to'. selected by the Engineering Committee of the the following reasons: wells in an effort to distribute the injecte per mechanical condition. producing wells on the same basic lease that ly assigned to the input well. individual companies to one input well in ord company. Franklin Petroleum Corporation Company or Operator By</pre>
011 Sands, from 2880 ' to 2885 Plugged back to'. Shot with 20quarts nitro glycerin Cleaned out to 2885'. Tubing 2849'-1". Packer-depth 2752'2". The input wells for this project were co Hills operators and were selected for Establishing a uniform spacing of input s evenly throughout the field. Selecting input wells that are in a pro Selecting input wells that have other p n make up the allowable production normal Endeavoring wherever possible to limit t to place such a burden on an individual Approved	<pre> '&' to'. selected by the Engineering Committee of the the following reasons: wells in an effort to distribute the injecte per mechanical condition. producing wells on the same basic lease that ly assigned to the input well. individual companies to one input well in ord company. Franklin Petroleum Corporation By</pre>
011 Sands, from 2880 ' to 2885 Plugged back to'. Shet with 20quarts mitro glycerin Cleaned out to 2885'. Tubing 2849'-1". Packer-depth 2752'2". The input wells for this project were co Hills operators and were selected for Retablishing a uniform spacing of input s evenly throughout the field. Selecting input wells that are in a pro Selecting input wells that have other p n make up the allowable production normal Rudeavoring wherever possible to limit t to place such a burden on an individual Approved	<pre> '&' to'. selected by the Engineering Committee of the the following reasons: wells in an effort to distribute the injecte per mechanical condition. producing wells on the same basic lease that ly assigned to the input well. individual companies to one input well in ord company. Franklin Petroleum Corporation Company or Operator By</pre>

Association, Inc., and return at least one copy to us for our files.

*

bea youe.

bensions viloured eldanolis vilo edt ecuborg of bedeenper ests at noissimned as an input well for the returning of the gas to the formation,

iberorque al estion aint il

a good mechanical condition. There are no "That Hartzens" above the Loco Sand

•

Approval is hereby requested for use of the Franklin Petroleum, Coppedge #4, well

our Franklin Petroleum, Coppedge #4, meets the above requirements and is in

and the second sec

• •

ţ

to this well from other weils on the same lease on which this woll is located.

Windly send I approved copy to the Loco Hills Pressure Maintenence

a a transformation of the second s

•

and the second second

 $\mathcal{F}^{(1)}(\mathcal{F}^{(1)}) = \mathcal{F}^{(1)}(\mathcal{F}^{(1)}) = \mathcal{F}^{(1)}(\mathcal{F}^{(1$