Form 3160-5 (June 1990)

UNLED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

5.	Lease Designation and Serial No.
	NMLC049947A
6.	If Indian, Allottee or Tribe Name

SUNDRY NOTICES AND REPORTS ON WELLS	
to a second to drill or to deepen or reentry to a different	reservoir.

Do not use this form for proposals to drill or to deepen or reentry to a d Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well 8. Well Name and No. Oil Well WÏW Yates #2 2. Name of Operator 9. API Well No. (505) 748-1471)YATES PETROLEUM CORPORATION 30-015-04471 3. Address and Telephone No. 10. Field and Pool, or Exploratory Area 105 South 4th St., Artesia, NM 88210 Loco Hills Q-GB-SA 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 11. County or Parish, State 1650' FNL & 330' FWL (SWNW) of Section 6-T18S-R30E Eddy Co., NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12 TYPE OF ACTION TYPE OF SUBMISSION Change of Plans Abandonment X Notice of Intent **New Construction** Recompletion Non-Routine Fracturing Plugging Back Subsequent Report Water Shut-Off Casing Repair Conversion to Injection Altering Casing Final Abandonment Notice Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* CONTINUED FROM PREVIOUS PAGE: CONTINUED: POOH. (If circulation is achieved, bring cement to surface in annulus and force outside 8-5/8" after cement is circulated). If cement has not been circulated, will perforate 4 holes at 60'. Attempt to establish circulation to surface through 7" X 8-5/8" annulus. Squeeze cement surface plug down 7" casing with returns through the 7" X 8-5/8" annulus. When cement is circulated, close annulus valve to force cement outside 8-5/8" casing. If cement was circulated outside casing in Step 7, will set at surface plug from 60' Install regulation abandonment marker. 10. 14. I hereby serify that the foregoing is true and correct Title __ Production Clerk Date August (This space for Federal of State office use)