

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Artesia, NM 88210

Form approved.
Budget Bureau No. 1004-013-
Expires August 31, 1985

clsf

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

OCT 25 11 40 AM '87
RECEIVED
CARRIZO VALLEY
AREA HEADQUARTERS
NOV 18 '87
O.C. D.
ARTESIA, OFFICE

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ P&A (WIW)
2. NAME OF OPERATOR Yates Petroleum Corporation
3. ADDRESS OF OPERATOR 105 South 4th St., Artesia, NM 88210
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface
990 FNL & 911 FWL, Sec. 6-T18S-R30E

5. LEASE DESIGNATION AND SERIAL NO. NM 021095
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME Yates "A"
9. WELL NO. 9
10. FIELD AND POOL, OR WILDCAT Loco Hills-Q-G-SA
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Unit D, Sec. 6-T18S-R30E
12. COUNTY OR PARISH Eddy
13. STATE NM

14. PERMIT NO.
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3550' KB

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☒
CHANGE PLANE ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☐
REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Propose to go in hole with impression block to investigate nature of 5½" casing part at 960' as detected by earlier work on well. If possible 5½" casing will be pulled from above part to run offset hook in an attempt to straighten casing below part to make reentry of lower part of hole possible. If casing cannot be pulled, a mill will be run in attempt to cut back into lower part of casing. If lower part of well cannot be reentered, a cement plug will be spotted at the casing part and tagged if possible.

Upper portion (above Salt section) will be plugged by setting a CIBP in 5½" or 8½" casing at approximately 450' depending on whether 5½" could be pulled. Casing will be perforated at approximately 400'. Cement will be spotted through tubing on bridge plug to approximately 50' above perforations to provide cement to go outside perforations. Plug will be tagged and cement will be resotted until fill above perforations are tagged. Casing will be perforated at approximately 100'. Cement will be pumped down casing in sufficient amount to circulate or leave 50-100 sacks outside of casing and cement to surface inside of casing.

Verbal approval of the foregoing plan given by Peter Chester, BLM, Roswell, NM, on 10-19-87.

18. I hereby certify that the foregoing is true and correct

SIGNED Albert R. Stall TITLE Engineer DATE 10-27-87

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE 11-17-87
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side