

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 1004-013  
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

LC-047269 (a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different level.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> WIW	2. NAME OF OPERATOR YATES PETROLEUM CORPORATION	3. ADDRESS OF OPERATOR 207 South 4th Street, Artesia, NM 88210	4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FSL & 660' FWL of Sec. 7, T-18, R-30E	5. UNIT AGREEMENT NAME W. LOCO HILLS G 4S UT	6. FARM OR LEASE NAME TRACT 1	7. WELL NO.	8. FIELD AND POOL, OR WILDCAT LOCO HILLS	9. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 7-18S-30E NMPM	10. COUNTY OR PARISH Eddy	11. STATE New Mexico
12. PERMIT NO.	13. ELEVATIONS (Show whether DF, RT, GR, etc.)									

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRAC-TURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

OTHER

WELL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRAC-TURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

We plan to repair this well properly and return it to water injection.

1. Fish packer cone and rubber.
2. Run bond log and casing inspection log.
3. If 5 1/2" casing is repairable then back off 2 joints of casing, replace with new 5 1/2" casing and install well head on 5 1/2" casing.
4. Perforate at top of existing cement and squeeze to bottom of salt.
5. Perforate at 250' and squeeze to surface.
6. If 5 1/2" casing could not be repaired then run 4 1/2" streamline casing to top of liner at 2600' and cement back to surface. Install wellhead on 4 1/2" casing.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature]

TITLE Engineering Technician

DATE 9/25/84

(This space for Federal or State office use)

APPROVED BY

TITLE AREA MANAGER  
CARLSBAD RESOURCE AREA

DATE 10-26-84

CONDITIONS OF APPROVAL, IF ANY:

Subject to  
Like Approval  
by State

\*See Instructions on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.