

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. DIV-1
1301 W. Grand Avenue
Artesia, NM 88210

FORM APPROVED
BMP No. 1004-0135
Expires November 30, 2000

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or re enter an
an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on reverse side

1 Type of Well

☒ Oil well ☐ Gas Well ☐ Other

2 Name of Operator

Yates Petroleum Corporation

a. Address

105 S. 4th St., Artesia, NM 88210

3b. Phone No. (include area code)

505-748-1471

4 Location of Well

(Footage, Sec., T., R., M., OR Survey Description)

660' FSL & 660' FWL of Sec. 7-T18-R30E

5. Lease Serial No.

LC-047269 (a)

6. If Indian, Allottee or Tribe Name

7 If Unit or CA/Agreement, Name and/or No.

W. Loco Hills G4S Unit

8. Well Name and No.

Tract 1 #4

9. API Well No.

30-015-03512

10. Field and Pool, or Exploratory Area

Loco Hills

11. County or Parish, State

Eddy, New Mexico

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☒ Notice of Intent

☐ Acidize

☐ Deepen

☐ Production (Start/Resume)

☐ Water Shut-Off

☐ Alter Casing

☐ Fracture Treat

☐ Reclamation

Well Integrity

☐ Subsequent Report

☐ Casing Repair

☐ New Construction

☐ Recomplete

☐ Other

☐ Change Plans

☒ Plug and Abandon

☐ Temporarily Abandon

☐ Final Abandonment Notice

☐ Convert to Injection

☐ Plug Back

☐ Water Disposal

APPROVED

JAN 14 2002

LES BABYAK
PETROLEUM ENGINEER

13 Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond no. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleation in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have completed, and the operator has determined that the site is ready for final inspection.)

Propose to plug & abandon as follows:

- TOH with 2 3/8" tubing.
- TIH with WL set CIBP, set CIBP @ 2500' TOH. TIH with tubing tag CIBP load hole with plugging mud. Spot 25 sack Class C Cement plug from 2,230' to 2500'.
- Perforate 4 1/2" casing with 6 holes @ 1150'. And 6 holes @ 452'.
- TIH with WL set cement retainer and set retainer @ 1100', TOH. TIH with tubing string into retainer and establish an injection rate. Squeeze with 75 sacks Class C Cement. Leave 35' of cement on top of retainer. TOH with tubing.
- TIH with WL set cement retainer, and set retainer @ 352'. (cont. of previous page)

14 I hereby certify that the foregoing is true and correct

Name (Printed/Typed)

Rusty Klein

Title

Operations Technician

Date

May 22, 2001

Signature

Rusty Klein by Elena Marquez

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

RECEIVED
2001 JAN 3 PM 1 03
BUREAU OF LAND MANAGEMENT
ARLINGTON FIELD OFFICE

**SEE ATTACHED FOR
CONDITIONS OF APPROVAL**

2000 HC 1111
1111 1111
1111 1111

1111
1111
1111

1111
1111
1111
1111
1111

West Loco Hills G4S Unit
660' FSL, 660' FWL, Sec. 7-T18S-R30E
Eddy County, New Mexico

TOH. TIH with tubing. Sting in to retainer and establish circulation.
Squeeze with 75 sacks of Class C cement from 352' to 452'. Leave 35'
of cement on retainer. TOH with tubing.

6. Spot 15 sacks Class C Cement plug at surface.
7. Install regulation abandonment marker.

NOTIFY BLM – Carlsbad (505-234-5190)
& OCD – Artesia (505-748-1283) 24 Hours PRIOR TO COMMENCING
PLUGGING OPERATIONS

Rusty Klein
Operations Technician
May 22, 2001