

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN .PLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER DRY HOLE

2. NAME OF OPERATOR  
FRANKLIN, ASTON & FAIR, LTD.

3. ADDRESS OF OPERATOR  
P. O. BOX 1090, ROSWELL, NEW MEXICO 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface  
1650' FWL - 330' FSL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3495' GR

5. LEASE DESIGNATION AND SERIAL NO.

LC 063621

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

MASTELLER

9. WELL NO.

1-A

10. FIELD AND POOL, OR WILDCAT

11. SEC., T., R., M., OR BLM. AND  
SURVEY OR AREA

SEC. 8 - 18S - 30E

12. COUNTY OR PARISH 13. STATE

EDDY COUNTY NEW MEXICO

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data:

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

XX

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

On March 24, 1976, pursuant to a telephone conversation with Mr. Knauf, this well was plugged and abandoned, as follows, when it was determined the two-inch (2") tubing at 2876 feet could not be pulled.

Pumped 50 sacks cement to bottom of tubing and left shut-in overnight, which stopped the flow of water;

Perforated tubing at 1690 feet, had heavy flow of water, pumped 50 sack cement plug, followed by another 50 sacks cement, which stopped the flow of water;

Perforated two (2) holes at 1250 feet at base of Salt and pumped 100 sack plug and shut in with 400 PSI pressure;

Perforated two (2) holes at 460 feet and pumped 50 sacks cement in and out base of 8 5/8 inch casing;

Placed 10 sack plug and marker at surface.

The cementing was done by Halliburton and inspected by U.S.G.S., Artesia.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Grant M. Smith*

TITLE

Geologist

DATE

April 2, 1976

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

\*See Instructions on Reverse Side

*posted  
D & A  
ID-2  
4-9-76*