

(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN APPLICATION*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

LC 063621

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

MASTELLER, A

9. WELL NO.

3-A

10. FIELD AND POOL, OR WILDCAT

11. SEC. T. R. M. OR BLK. AND SURVEY OR AREA

SEC. 8 - 18S - 30E

12. COUNTY OR PARISH

EDDY COUNTY

13. STATE

NEW MEXICO

1. OIL WELL ☐ GAS WELL ☒ OTHER DRY HOLE

2. NAME OF OPERATOR

FRANKLIN, ASTON & FAIR, Inc. LTD.

3. ADDRESS OF OPERATOR

P. O. BOX 1090, ROSWELL, NEW MEXICO 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

1650' FSL - 1650' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3499' DF

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

On March 24, 1976, this well was plugged and abandoned as follows

Two-inch (2") tubing was run to the bottom of the hole, 2941 feet, and the hole was circulated with heavy mud:

25 sack plug 2941 to 2841 feet across Loco Hills Sand;
25 sack plug 1250 to 1150 feet at base of Salt;
25 sack plug 500 to 400 feet in and out base of 8 5/8 inch casing;
10 sack plug and marker at surface.

The cementing was done by Halliburton as per U.S.G.S. approval October 15, 1974. Mr. Gordon, U.S.G.S., Artesia, inspected last plug.

18. I hereby certify that the foregoing is true and correct.

SIGNED

Erant M. Smith

TITLE

Geologist

DATE

April 2, 1976

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

RECEIVED
APR - 5 1976
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

past
P1a-2
ID-2
4-9-76