

Form 9-331a
(Feb. 1951)

(SUBMIT IN TRIPLICATE)

Land Office N.M.Lease No. 0968Unit 5**APPROVED**

FEB 17 1959

ROBERT F. EVANS
ACTING DISTRICT ENGINEERUNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	<u>Temporary</u>
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	<u>X</u>
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Feb'y. 14, 1959Well No. Sergeant is located 330 ft. from N line and 330 ft. from E line of sec. 9185 (Range) 300 (Meridian)Undesignated (County or Subdivision) N.M. (State or Territory)The elevation of the derrick floor above sea level is 3525 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

This hole is T.A. 3826'. The hole was pumped full of heavy aquagel mud. The 8 5/8" O.D. surface pipe is still in hole. There is an 8 5/8" O.D. casing nipple screwed in the top collar of surface pipe and extending 6' above the surface ground level and a 8 5/8" O.D. x 2" swaged nipple screwed in the top of casing nipple. There is a 2" H.P. valve screwed on the top of swaged nipple with a 2" ball plug screwed in the 2" valve.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Franklin Aston & Fair, Inc.Address Box 218
Los Alamos N.M.By O. C. RogersTitle Gen'l. Sup't.