



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

20-015-04526

Budget Bureau No. 42-R358.4.
Approval expires 12-31-60.

Land Office **Las Cruces**
Lease No. **047269-8**
Unit **Canfield**
NM 025614

RECEIVED

MAY 16 1962
A. R. SKOWN
ACTING DISTRICT ENGINEER

SUNDRY NOTICES AND REPORTS ON WELLS

MAY 21 1962

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	<input type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	<input type="checkbox"/>
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	<input type="checkbox"/>
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	<input type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 3, 1962

Well No. **5-8** is located **1980** ft. from **[N]** line and **1980** ft. from **[E]** line of sec. **18**
C-SE-W **18** **18** **30** **NWPM**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Loco Hills **Eddy** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **3516** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

On November 20 to 26, 1950 plugged and abandoned well.

1. Set 10 sack cement plug at 3620' total depth.
2. Mud hole from total depth to surface.
3. Bust 7' casing and pulled 1248' & 9' of same.
4. Set 10 sack cement plug at 1250' in stub of 7' casing.
5. Set 10 sack cement plug into and below 8 1/4' casing at 426'.
6. Bust 8 1/4' casing and pulled 111' & 9' of same.
7. Set 10 sack cement plug at 117' in stub of 8 1/4' casing.
8. Cement surface of hole and installed 4' pipe extended 6' above surface of ground.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Franklin, Aston & Fair, Inc.**

Address **P. O. Box 1090**
Roswell, New Mexico

By **G. C. Rogers**
General Superintendent