

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN _____
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug or to different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. LC-028978-a	
2. NAME OF OPERATOR TEXACO Inc.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME NONE	
3. ADDRESS OF OPERATOR P. O. Box 728 - Hobbs, New Mexico		7. UNIT AGREEMENT NAME NONE	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Well located 661' from the North Line, and 669' from the West Line of Section 22, 18-S, R-30-E, Eddy County, New Mexico.		8. FARM OR LEASE NAME L.R. Manning Fed. "a"	
14. PERMIT NO. Regular		9. WELL NO. 3	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3474' (D. F.)		10. FIELD AND POOL, OR WILDCAT Leo	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 22, 18-S, R-30-E	
		12. COUNTY OR PARISH Eddy	
		13. STATE N. M.	

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

SUBSEQUENT REPORT OF:

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

We propose to plug and abandon subject well as follows:

NOTE: 10 3/4" O. D. Casing was cemented at 625', with cement circulated.

5 1/2" O. D. Casing was cemented at 3285', with cement circulated.

Production was from 4 3/4" Open Hole, 3285' to 3350'.

1. Pull rods and all pump equipment.
2. Spot 35 Sx. cement from total depth of 3350' to 3050'.
3. Spot 100 Sx. cement from 1460' to 525' inside 5 1/2" O. D. Casing.
4. Spot 10 Sx. cement as surface plug, from 100' to 0' inside 5 1/2" O. D. Casing.
5. Clean location for inspection as per the United States Department of The Interior Geological Survey regulations, install 4" marker extending 4' above ground level.

18. I hereby certify that the foregoing is true and correct

SIGNED

Dan Gillett

TITLE Assistant District
Superintendent

DATE October 29, 1965

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL

APPROVED

NOV 1

RUDOLPH C. BAUER, JR.
ACTING DISTRICT ENGINEER

TITLE

all operations

*See Instructions on Reverse Side