

Heaving plug—Material Length Depth set
 Adapters—Material Size

SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out
5½"	17'	NitroGlycerin	80 qts	9/5/42	3261-78	3279'

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet
 Cable tools were used from feet to feet, and from feet to feet

DATES

....., 19..... Put to producing September 8, 1942

The production for the first 24 hours was barrels of fluid of which % was oil; %
 emulsion; % water; and % sediment. Gravity, °Bé.

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

....., Driller C. F. Shannon, Driller
 G. C. Pratt, Driller
 George Bowers, Driller

FORMATION RECORD

FROM	TO	TOTAL FEET	FORMATION
0	60	60	Sand
60	415	355	Red Beds
415	465	50	Gyp & Anhydrite
465	475	10	Red Bed
475	480	5	Gyp
480	505	25	Blue Shale
505	610	95	Red Bed
610	625	15	Gyp
625	1295	670	Salt
1295	1330	35	Anhydrite
1330	1470	140	Salt
1470	2760	1290	Anhydrite
2760	2810	50	Red Sand
2810	3040	230	Anhydrite
3040	3170	130	Lime
3170	3190	20	Red Sand
3190	3200	10	Lime
3200	3225	25	Sandy Lime
3225	3265	40	Lime
3265	3275	10	Oil Sand-Natural Production 15-20 Bbls/day
3275	3279	4	Lime. TD

(OVER)

6-6745