

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

(Other Instructions on Reverse Side)

EXPIRES AUGUST 31, 1988

3. LEASE DESIGNATION AND SERIAL NO

LC-028978-B

8. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR  
Texaco Inc. ✓

3. ADDRESS OF OPERATOR  
P. O. Box 728, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)  
At surface  
Unit Letter C, 660' FNL & 1980' FWL

14. PERMIT NO.  
30-015-04561

15. ELEVATIONS (Show whether DF, RT, GR, etc.)  
3460' DF

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
North Benson Queen Unit

9. WELL NO.  
36

10. FIELD AND POOL, OR WILDCAT  
North Benson Queen Grayburg

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 34, T18S, R30E

12. COUNTY OR PARISH  
Eddy

13. STATE  
NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐ PULL OR ALTER CASING ☐  
FRACTURE TREAT ☐ MULTIPLE COMPLETE ☐  
SHOOT OR ACIDIZE ☐ ABANDON\* ☐  
REPAIR WELL ☐ CHANGE PLANS ☐  
(Other) ☐

WATER SHUT-OFF ☐ REPAIRING WELL ☐  
FRACTURE TREATMENT ☐ ALTERING CASING ☐  
SHOOTING OR ACIDIZING ☒ ABANDONMENT\* ☐  
(Other) ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

- 6-13-88 MIRU pulling unit. Pull rods and pump. Install BOP. Tag PBTD. Pull tubing.
- 6-14-88 RIH with bit and scraper to + 3060'. POH. Clean out fill with bailer to PBTD at 3400'. RIH with tubing. Spot scale converter. SION.
- 6-15-88 Spot acid from 2777'-3400'. POH. RIH with packer on 2-7/8" tubing. Set packer at + 2700'. Load backside with produced water. Acidize the perms at 2827'-3050' and open hole from 3102'-3400' with 1500 gallons of 15% NEFE acid and 750# rocksalt in gelled brine. Flush to bottom. Release packer. POH. Run production equipment. Place well on production.
- 7-1-88 On 24 hr. OPT, pump 10 BO, 5 BW, Gas TSTM. Production prior to workover - 7 BOPD, 17 BWPD.

18. I hereby certify that the foregoing is true and correct 397-3571  
SIGNED J. A. Hearn TITLE Hobbs Area Superintendent DATE August 23, 1988  
(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_

ACCEPTED FOR RECORD  
DATE \_\_\_\_\_

SEP 15 1988

\*See Instructions on Reverse Side

SJS  
CARLSBAD, NEW MEXICO