
Co, I to St.

Budget Bureau No. 42-R358.4. Approval expires 12-31-60.

Land Office NOW Mexico

Unit .....

Lease No. 111 03894



## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

(SUBMIT IN TRIPLICATE)

		SUBSEQUENT	REPORT OF WATER SHU	IT-OFF	
NOTICE OF INTENTION TO CHANGE P		II -	REPORT OF SHOOTING		
NOTICE OF INTENTION TO TEST WATE	ER SHUT-OFF	il	REPORT OF ALTERING		ı
NOTICE OF INTENTION TO RE-DRILL	OR REPAIR WELL	III	REPORT OF RE-DRILLIN		
NOTICE OF INTENTION TO SHOOT OR	ACIDIZE	ii .	REPORT OF ABANDONM		
NOTICE OF INTENTION TO PULL OR A	LITER CASING		ARY WELL HISTORY		
NOTICE OF INTENTION TO ABANDON	WELL				
(INDICAT	TE ABOVE BY CHECK MARK	NATURE OF REPORT	, NOTICE, OR OTHER DAT	ra)	
		******	Ар	ril 16	19.
/Texaco Federa		(N.I.)			·
Well No. # 1 is locat	ed 495 ft. from	$\mathbf{A} = \left\{ egin{array}{c} \mathbf{N} \\ \mathbf{X} \end{array} \right\}$ line and	<b>820</b> ft. from	line of s	sec. 34
NE NE 34 (4 Sec. and Sec. No.)		• /			
N. Benson (Field)	Eddy (County o	or Subdivision)	IV.	ew Mexic	0
		<b>3448</b> G	round		
state manner of anni expected deptile to	chiective sands, show six	es weights and lan	the of proposed seeings	. indianta modeli	:-b
ded 4 1/2" casing with	objective sands; show siz ing points, and all o h water, ran t				
ded 4 1/2" casing with ng. Rigged up jacks led 2330, 51' casing. ks cement at 1675', r ks in top of 8 5/8" cas	h water, ran t and shooting li Ran tubing in an 25 sacks ce	ubing and ine. Shot of hole. Lose iment at 63	5 sack plug a  ff 4 1/2" casi  led hole with  0'. Pulled tul  well designs	t 3100: Ping at 2325 mud. Raming and ration and le	ulled 5. n 27 an 5
ded 4 1/2" casing withing. Rigged up jacks led 2330,51' casing. as cement at 1675', rais in top of 8 5/8" cas	h water, ran t and shooting li Ran tubing in an 25 sacks ce	ubing and ine. Shot of hole. Lose iment at 63	5 sack plug s If 4 1/2" casi led hole with O'. Pulled tub	at 3100: Ping at 2325 mud. Raing and ration and lo	ulled 5. n 27 an 5
ded 4 1/2" casing with ng. Rigged up jacks led 2330,51' casing. its cement at 1675', r its in top of 8 5/8" cas	h water, ran t and shooting li Ran tubing in an 25 sacks ce	ubing and ine. Shot of hole. Lose iment at 63	5 sack plug a  ff 4 1/2" casi led hole with  0'. Pulled tul well designs	at 3100: Ping at 2325 mud. Rai ming and ra tion and lo	ulled 5. n 27 an 5 ocation
ded 4 1/2" casing withing. Rigged up jacks led 2330, 51' casing. iks cement at 1675', riks in top of 8 5/8" castronation. D&A.	h water, ran t and shooting li Ran tubing in an 25 sacks ce sing. Set 4" m	ubing and ine. Shot of hole. Lose ament at 63 narker with	5 sack plug a  ff 4 1/2" casi led hole with  0'. Pulled tul well designs  APR	ing at 2325 mud. Raining and ration and lo	ulled 5. n 27 an 5 ocation
	h water, ran t and shooting li Ran tubing in an 25 sacks ce sing. Set 4" m	ubing and ine. Shot of hole. Lose ament at 63 narker with	5 sack plug a  ff 4 1/2" casi led hole with  0'. Pulled tul well designs  APR	ing at 2325 mud. Raining and ration and lo	ulled 5. n 27 an 5 ocation
ded 4 1/2" casing withing. Rigged up jacks led 2330, 51' casing. iks cement at 1675', riks in top of 8 5/8" cas remation. D&A.	h water, ran t and shooting li Ran tubing in an Z5 sacks ce sing. Set 4" m	ubing and ine. Shot of hole. Lose ament at 63 narker with	5 sack plug a  ff 4 1/2" casi led hole with  0'. Pulled tul well designs  APR	ing at 2325 mud. Raining and ration and lo	ulled 5. n 27 an 5 ocation
ded 4 1/2" casing withing. Rigged up jacks led 2330, 51' casing. iks cement at 1675', riks in top of 8 5/8" castronation. D&A.	h water, ran tand shooting li Ran tubing in an 25 sacks ce sing. Set 4" m	ubing and ine. Shot of hole. Lose ament at 63 narker with	5 sack plug a  ff 4 1/2" casi led hole with  0'. Pulled tul well designs  APR	ing at 2325 mud. Raining and ration and lo	ulled 5. n 27 an 5 ocation
ded 4 1/2" casing withing. Rigged up jacks led 2330, 51' casing. as cement at 1675', raises in top of 8 5/8" cas remation. D&A.  Tunderstand that this plan of work Company Reading and address 1101 Philtow	h water, ran tand shooting li Ran tubing in an 25 sacks ce sing. Set 4" m	ubing and ine. Shot of hole. Lose ament at 63 narker with	5 sack plug a  ff 4 1/2" casi led hole with  0'. Pulled tul well designs  APR	ing at 2325 mud. Raining and ration and lo	ulled 5. n 27 an 5 ocation
ded 4 1/2" casing withing. Rigged up jacks led 2330, 51' casing. as cement at 1675', rais in top of 8 5/8" cas rmation. D&A.  I understand that this plan of work company. Reading and	h water, ran tand shooting li Ran tubing in an 25 sacks ce sing. Set 4" m	ubing and ine. Shot of hole. Lose ament at 63 narker with	5 sack plug a  ff 4 1/2" casi led hole with  0'. Pulled tul well designs  APR	ing at 2325 mud. Raining and ration and lo	ulled 5. n 27 an 5 ocation