

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☒ Re-Plug Well

2. NAME OF OPERATOR ☒ TEXACO Inc.

3. ADDRESS OF OPERATOR
P. O. Box 728, Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE:
AT TOP PROD. INTERVAL: Unit Letter 'A'
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

(other) to: Re-plug well

SUBSEQUENT REPORT OF:

RECEIVED

AUG 13 1979

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

5. LEASE
NM 27281

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
-

7. UNIT AGREEMENT NAME
-

8. FARM OR LEASE NAME
TEXACO Federal

9. WELL NO.
1

10. FIELD OR WILDCAT NAME

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 34, T-18-S, R-30-E

12. COUNTY OR PARISH
Eddy

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TEXACO Inc. proposes to re-enter & re-plug subject P & A well formerly operated by Reading & Bates. This operation is to comply with letter from NMOC D, 4-30-79, informing TEXACO that the well does not contain the injection interval in the offset injection wells of TEXACO'S North Benson Queen Unit

1. Rig up. Remove Dry Hole Marker, Install BOP.
2. Drill out cement plugs to top of 4 1/2" Csg. (Approx. 2330')
3. Spot 35 sx. plug - 100' across 4 1/2" Csg Stub.
4. Spot 105 sx. plug from 1800' - 1400'.
5. Spot 25 sx. plug from 630' - 430'.
6. Spot 10 sx. plug from 180' - surface.
7. Install Dry Hole Marker. Clean up location.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED George H. Stewart TITLE Asst. Dist. Supt. DATE 8-9-79

(Orig. Sgd.) GEORGE H. STEWART (This space for Federal or State office use)

APPROVED BY _____ TITLE DISTRICT ENGINEER DATE NOV 13 1979

CONDITIONS OF APPROVAL, IF ANY: