

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☐ well ☒ other Re-Plug Well

2. NAME OF OPERATOR
TEXACO Inc.

3. ADDRESS OF OPERATOR
P. O. Box 728, Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 49° 10' N 125° E
AT TOP PROD. INTERVAL: Unit Letter 'A'
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input checked="" type="checkbox"/>
(other) Re-Plug	

5. LEASE -

6. IF INDIAN, ALLOTTEE OR TRIBE NAME -

7. UNIT AGREEMENT NAME -

8. FARM OR LEASE NAME
TEXACO - Federal

9. WELL NO. 1

10. FIELD OR WILDCAT NAME -

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 34, T-18-S, R-30-E

12. COUNTY OR PARISH Eddy

13. STATE New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TEXACO Inc. re-entered & re-plugged subject P&A well, formerly operated by Reading & Bates, in the following manner:

1. Rigged up. Remove Dry Hole Marker.
2. Drill out surface plug in 8 5/8" Csg to 30'. Install BOP. Clean out to 2300'.
3. Spot 300 sx. Class 'C' cement plug from 2300' - 616'.
4. Spot 12 Bbls. gel in cotton seed hull for plug @ 616'. Followed w/60 sx. Class 'C' cement plug from 616' - 525'.
5. Spot 40 sx. cement plug @ surface.
6. Set Dry Hole Marker. Job complete 12-14-79.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED George J. Stewart TITLE Asst. Dist. Supt. DATE 3-26-80

(This space for Federal or State office use)
APPROVED BY George J. Stewart TITLE AGING DISTRICT ENGINEER DATE APR 03 1980
CONDITIONS OF APPROVAL, IF ANY: