

AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

RECEIVED

WELL RECORD

SEP 24 1962

R. E. E.
ARTESIA: 877EE

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

McCoy & Stevens

(Company or Operator)

Texaco-State

(Lease)

Well No. 1, in SW $\frac{1}{4}$ of SE $\frac{1}{4}$, of Sec. 16, T. 18S, R. 30E, NMPM.

Leo

Pool,

Eddy

County.

Well is 1650 feet from East line and 330 feet from South line

of Section 16. If State Land the Oil and Gas Lease No. is KK E-9262

Drilling Commenced 4:00 PM 7-23-62, 19 . Drilling was Completed 12:00 PM 8-23-62, 19

Name of Drilling Contractor Kincaid & Watson

Address 207 North 4th Street, Artesia, New Mexico

Elevation above sea level at Top of Tubing Head 3464. The information given is to be kept confidential until , 19

OIL SANDS OR ZONES

No. 1, from None to . No. 4, from to

No. 2, from to . No. 5, from to

No. 3, from to . No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 365 to 375 feet.

No. 2, from 530 to 545 feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8-5/8"	24#	used	614'	Larkin	310	-	Surface Casing

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. BAGS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11"	8-5/8	614	50 sz.	pump & plug	-	-

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

No shows of oil and gas encountered during drilling. Loaded hole with Aqua Gel mud.
Spotted 20 sack plug 3350-3290, 20 sack plug 1300 to 1240, 20 sack plug 625-565,
10 sack plug at surface.

Result of Production Stimulation

Depth Cleaned Out

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 3350 feet, and from 0 feet to 3350 feet.
Cable tools were used from 0 feet to 3350 feet, and from 0 feet to 3350 feet.

PRODUCTION

Put to Producing 19

OIL WELL: The production during the first 24 hours was barrels of liquid of which % was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity.

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy.		T. Devonian	
T. Salt		T. Silurian	
B. Salt		T. Montoya	
T. Yates		T. Simpson	
T. 7 Rivers	1894	T. McKee	
T. Queen	2560	T. Ellenburger	
T. Grayburg	2980	T. Gr. Wash.	
T. Loco Hills	3200	T. Granite	
T. Glorieta			
T. Drinkard			
T. Tubbs			
T. Abo			
T. Penn.			
T. Miss.			

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0		10	Surface Gravel	2300		2315	Lime
10		25	Caliche	2315		2350	Gray Lime
25		80	Shale	2350		2390	Anhydrite
80		100	Sand & Shale	2390		2450	Anhydrite & Lime
100		130	Gravel	2450		2550	Red Sand
130		190	Red Rock	2550		2600	Lime
190		265	Shale	2600		2620	Anhydrite
265		365	Red Beds	2620		2680	Lime
365		385	Anhydrite	2680		2780	Anhydrite
385		465	Red Beds & Anhydrite	2780		2807	Sand
465		480	Anhydrite	2807		2825	Lime
480		510	Anhydrite & Red Rock	2825		2850	Lime & Anhydrite
510		535	Anhydrite	2850		2898	Lime
535		550	Sand & Lime	2898		2910	Sandy Lime
550		595	Anhydrite	2910		2925	Anhydrite & Lime
595		760	Salt	2925		2960	Sand & broken lime
760		790	Anhydrite	2960		2981	Sand & Lime
790		1300	Salt	2981		2990	Gray Lime
1300		1910	Anhydrite	2990		3010	Lime
1910		1945	Broken Lime	3010		3025	Sandy Lime
1945		1975	Lime	3025		3055	Lime
1975		1995	Lime & Anhydrite	3055		3095	Sandy Lime
1995		2025	Lime	3095		3204	Lime
2025		2085	Anhydrite	3204		3250	Sand
2085		2220	Lime	3250		3275	Broken Lime
2220		2285	Anhydrite & Lime	3275		3305	Lime
2285		2300	Lime, Anhy. & Sand	3305		3350	Sandy Lime - TD

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Company or Operator McCoy & Stevens Address 606 Security Nat. Bk. Bldg., Roswell, N. M.
Name W. B. McCoy Position Title Partner

9-21-62

(Date)