

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐  
well well other

2. NAME OF OPERATOR

WILLIAM A. & EDWARD R. HUDSON ✓

3. ADDRESS OF OPERATOR

Box #198, Artesia, New Mexico 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' from south and west lines of  
AT TOP PROD. INTERVAL: Sec. 24-17S-31E.  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☒  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) \_\_\_\_\_

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE

LC-029415-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME RECEIVED BY

8. FARM OR LEASE NAME DEC 01 1983  
Puckett "A"

9. WELL NO. O. C. D.  
12 ARTESIA, OFFICE

10. FIELD OR WILDCAT NAME  
Maljamar

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 24-17S-31E

12. COUNTY OR PARISH Eddy 13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

On Nov. 28, 1983, water appeared at the surface between the 8-5/8" casing cemented at 590' and the 7" production string cemented at 3283'. Flow is approximately 50 barrels of water per day at low pressure. Also a hole in 8-5/8" casing is indicated at approximately 60' from the surface. Estimated top of salt is 700'. It is proposed to run a cement bond log to determine top of cement behind the 7" casing. After studying the log, a final remedial program will then be submitted.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Ralph L. Gray TITLE Consultant DATE November 30, 1983  
(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: