5-USGS-Eddy County 1-EF, Foreman 1-NMOCD-Artesia	C/SF
1-NMOCD-Artesia -File 1-PWS-Engineer Form 9-331	Form Approved.
Dec. 1973	Budget Bureau No_42-R1424
UNITED STATES DEPARTMENT OF THE INTERIOR	5. LEASE
	LC-029418 (b) 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
File GEOLOGICAL SURVEY	<u> </u>
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9–331–C for such proposals.)	Skelly Unit
	Skelly Unit 3 3 5 1981
well well other Injection well	9. WELL NO.
2. NAME OF OPERATOR	<u>83 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7</u>
Getty Oil Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR P. O. Box 730 Hobbs, New Mexico 88240	Grayburg-Jackson, Fren-7 Rivers 11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA होईई उक्किस
below.) AT SUBFACE. Unit Ltr. D 660' FNL & 660' FWL	Sec. 26, T-175, R=31E
AT SURFACE: UNIT LEF. D 660 FNL & 660 FWL AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH Eddy
AT TOTAL DEPTH:	14. API NO. CORTA E TESS
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3840' DF
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	3840 Dr
FRACTURE TREAT	
	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING AUG 18	1981 · · · · · · · · · · · · · · · · · · ·
CHANGE ZONES	
ABANDON* OIL & C (other) OIL & C	ALSURVEY 두 방법학계 및 방법국도 문문
ROSWELL, NEV	그는 그는 그는 것이 이야지 않는 것이 있는 것이 있는 것이 있는 것이 있는 것이 없는 것이 있는 것이 없는 것이 없다.
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stat including estimated date of starting any proposed work. If well is d	e all pertinent details, and give pertinent dates, lirectionally drilled, give subsurface locations and
measured and true vertical depths for all markers and zones pertiner	nt to this work.)*
 Rig up pulling unit. Install BOP. 	· · · · · · · · · · · · · · · · · · ·
3. Pull out of hole with tubing and packers	
4. Locate hole in casing.	· · · · · · · · · · · · · · · · · · ·
5. Squeeze hole in casing.	· · · · · · · · · · · · · · · · · · ·
6. Drill out cement.	사건가 있는 것은 것을 하는 것이 있는 것이 있는 것이 있다. 것은 것은 물건은 이 가운 것을 통하는 물건을 통하는 것이 있는 것이 있는 것이 있는 것이 있다.
 Run in hole with tubing and packers. Return to injection. 	
o. Retain to injection.	(* 11) 전 12 (12) 전 25 년 전 15 년 전 전 전 25 년 12 년 12 년 26 년 26 년 13 년 1
	· · · · · · · · · · · · · · · · · · ·
Subsurface Safety Valve: Manu. and Type	Set @ 5 Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED Dale R. Crockett TITLEArea Superinte	ndentoate
PFB (This space for Federal or State of	fice use)
APPROVED BY TITLE	
CONDITIONS OF APPROVAL, IF ANY:	
	AUG 2 1 1981
*See Instructions on Reverse	
	DISTRICT SUPERVISOR

t

·•

.