


APPROVE
JAN 11 1963

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office Las Cruces
Lease No. 029419 (b)
Unit Lynch "B"

RECEIVED

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	
Perforate & Fracture	XX

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Hobbs, New Mexico - January 9, 1963Well No. 5 is located 660 ft. from N line and 660 ft. from E line of sec. 27NE/4 NE/4 Sec. 27
(1/4 Sec. and Sec. No.)17-S
(Twp.)31-E
(Range)N.M.P.M.
(Meridian)Grayburg Jackson
(Field)Eddy
(County or Subdivision)New Mexico
(State or Territory)The elevation of the derrick floor above sea level is 3639 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

1. Move in and rig up pulling unit.
2. Pull rods and tubing.
3. Set Retractable Bridge Plug at approximately 3695'.
4. Selective perforate Grayburg Zone.
5. Fracture perforations with approximately 20,000 gallons sand-oil.
6. Pull Retractable Bridge Plug.
7. Return well to production.

I understand that this plan of work must receive approval in writing by the Geological Survey before operation may be commenced.

Company Shelly Oil CompanyAddress Box 38Hobbs, New MexicoBy (ORIGINAL SIGNED) H. E. AsbTitle Dist. Supt.RECEIVED
JAN 11 1963
U. S. GEOLOGICAL SURVEY
ARTEZIA, NEW MEXICO