

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NM Oil Cons
FEB 2 1980
HOBBS, NM 88241

FORM APPROVED
Budget Bureau No. 1004-0135
Expires March 31, 1993

C15F

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT -" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☐ Other ☒ Water Injection

2. Name of Operator

The Wiser Oil Company

3. Address and Telephone No.

8115 Preston Road, Suite 400, Dallas, TX 75225 (214)265-0080

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit A, 660' FNL & 660' FEL, Sec 27, T17S, R31E

5. Lease Designation and Serial No.

NM-98121

6. If Indian, Allote or Tribe Name

7. If Unit or CA, Agreement Designation

Skelly Unit

8. Well Name and No.

84

9. Well API No.

30-015-05423

10. Field and Pool, or Exploratory Area

Grayburg Jackson 7-Rivers-QN-GB-SA

11. County or Parish, State

Lea, New Mexico

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☒ Conversion to Injection
☐ Dispose Water

ACCEPTED FOR RECORD
JUL 2 9 1987
JCS

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form).

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this zone).*

03/13/97 MIRU Tyler WS #104. Worked stuck pump & NU BOP. Backed off rods & LD 1-1/4" x 12' PR, 1-1/2" x 6' PRL, 1-2" x 3/4" rod sub, 1-6' x 5/8" rod sub, 1-4' x 5/8" rod sub, 41-5/8" rods, & 57-5/8" rods. POH w/16 stands out of hole. Ran paraffin knife.

03/14/97 POH w/rods & tbg. LD 52 5/8" rods, 1-1/4" x 2 x 14 pump. RIH w/4-3/4" bit. 6 3-1/2" DC on 2-3/8" tbg. Tagged 3890' & pmpd 130 bbls. No circ. POH & LD 4-3/4" bit & 6 3-1/2" DC's. TIH w/ 5-1/2" R-4 pkr. to 3300'.

03/17/97 RU rvs unit & loaded tbg-csg annulus to 500#. Had to let air work out of csg. Held 500# for 30 min. POH w/2-3/8" tbg & R-4 pkr. RIH w/2-3/8" tbg to 3907'. RU HES & spid 30 sks Class "C" w/2% CaCl. POH w/2-3/8" tbg to 3800'. Rvsd hole clean. RU rvs unit & circ gas. POH & LD 127 jts 2-3/8" tbg.

03/19/97 RIH w/5-1/2" Baker J-Lok w/1.5 profile, on-off tool & 105 jts 2-3/8" IPC tbg. Set pkr @ 3297' w/10,000# tension. RU HES & pmpd 110 bbls. pkr fl & acidize perms f/3349'-3800' w 7500 gals 15% Fer-check acid & 2000# rock salt. Good block action.

03/20/97 Injection rate 300 BWPD @ 1200#.

Part ID 3
8-1-97
Prod 50
WIW

RECEIVED
JUL 29 1987

14. I hereby certify that the foregoing is true and correct

Signed: Linda Stepp Title Agent

Oil Cons DIV.
JUL 29 1987

(THIS SPACE FOR FEDERAL OR STATE OFFICE USE)

Approved By: _____ Title _____ Date _____

Conditions of approval, if any: