

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE *
(Other Instructions on
reverse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT - " for such proposals.)

1. OIL ☐ WELL GAS ☐ WELL OTHER ☐ WIW

2. NAME OF OPERATOR
The Wiser Oil Company

3. ADDRESS OF OPERATOR
P.O. Box 2568 Hobbs, New Mexico 88240 (505) 392-9797

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1980' FNL & 1980' FWL
Unit F

5. LEASE DESIGNATION AND SERIAL NO.
NM-098121

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
Skelly Unit

8. WELL NO.
96

9. API Well No.
30-015-05424

10. FIELD AND POOL, OR WILDCAT
Grayburg Jackson Seven Rivers QN-GB-SA

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA
Sec. 27-T17S-R31E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3823' DF

12. COUNTY OR PARISH
Eddy County

13. STATE
NM

16. Check Appropriate Box to indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT OFF ☐ PULL OR ALTER CASING ☐
FRACTURE TREAT ☐ MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐ ABANDON* ☐
REPAIR WELL ☐ CHANGE PLANS ☐

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐ REPAIRING WELL ☐
FRACTURE TREATMENT ☐ ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐ ABANDONMENT * ☐

(Other) Perforate Lower Grayburg

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS: (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

8/11/98 MIRU Pool Well Service. ND WH. NU BOP's. Drop WH slip into hole. Unset top pkr. Release short string. POH w/37 stands of 2-1/16" CS-Hydril tbg. ND BOP's. Pull slips on long string. Long string missing 1 slip. NU BOP's. Bottom pkr. would not release. Push down hole 10'. Would not go up.
8/12/98 RU Rotary WL. Ran free point. Tbg. stuck 73201'-3308'. Pull into tbg. to back off & tbg. came loose. POH w/tbg. LD dual pkr., 30 jts. int.-ext. coated pipe & AD-1 pkr. RIH w/4-3/4" bit, bit sub & 2-3/8" work string. Tag @ 3421'. Pull to 2221'.
8/13/98 RU ABC reverse unit. RIH to 3421' w/2-3/8" tbg. Drill scale to 3838'. Circulate clean. POH & LD tbg. RU HES & perforate Lower Grayburg 73543', 44', 45', 46', 71', 72', 73', 3612', 14', 95', 96', 97', 3735', 36', 37', 38', 48', 49', 50', 55', 56' & 57' w/1 SPF (22 holes). RD HES. RIH w/AD-1 pkr., 31 jts. EPC-IPC 2-3/8" tbg., Baker Model B pkr. & 73 jts. 2-1/16" CS Hydril tbg. ND BOP's. Set pkr. @ 3304'. w/15,000# tension. Dual @ 2327.35'. NU BOP's.
8/14/98 RIH w/stinger & 73 jts. 2-1/16" CS Hydril tbg. & 2' sub. Circulate pkr. fluid. Latch into pkr. Pull 15,000# tension. RDMO.

18. I hereby certify that the foregoing is true and correct.

SIGNED Mary Jo Turner
Mary Jo Turner

TITLE Production Tech II

DATE December 28, 2001

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

*See Instruction On Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.



