

'MOCC COPY

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-029420-b

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

SKELLY UNIT

8. FARM OR LEASE NAME

SKELLY UNIT

9. WELL NO.

91

10. FIELD AND POOL, OR WILDCAT

GRAYBURG JACKSON

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

28-17-31.

12. COUNTY OR PARISH

EDDY

13. STATE

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ X-INJECTION

2. NAME OF OPERATOR

GETTY OIL COMPANY ✓

3. ADDRESS OF OPERATOR

P. O. BOX 730, HOBBS, NEW MEXICO 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FNL & 660' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3771' D.F.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Brought cmt. above 7-Rivers

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 4-19-78. Rigged up E & H Well Service; pulled tubing and packer.
- Dresser Atlas ran Cement Bond Log 2860-1500' and found Top of Cement @ 2192'. No Bridges. Perforated 2 (.46") holes @ 2180'.
- 4-20-78. B. J. cemented thru perforations @ 2180' w/200 sxs. 50/50 Poz Mix, 4% Gel, 6# Salt/sk. and 200 sxs. Class "C" Cement w/2% CaCl; and displaced cement to 2080'.
- Bennett Wireline Company ran Temperature Survey and found Top of Cement @ 1360'. O:K.
- 4-22-78. Drilled cement to 2190' and tested casing w/500# for 15 min. O:K.
- 4-24-78. Ran Howco R-4 packer; 90 jts. 2-3/8" duoline tubing (2794'); set @ 2798'; circulated w/treated water and put well back on injection.

RECEIVED
MAY 11 1978
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

ORIGINAL SIGNED BY

18. I hereby certify DALE R. CROCKETT is the authorized representative and correctSIGNED Dale R. CrockettTITLE AREA SUPERINTENDENTDATE MAY 9, 1978

(This space for Federal or State office use)

APPROVED BY Joe J. Lara
CONDITIONS OF APPROVAL, IF ANY:TITLE ACTING DISTRICT ENGINEERDATE MAY 12 1978