

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Oil & Gas Division

FORM APPROVED
Budget Bureau No. 1004-0135
Expires March 31, 1993

015F

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other WIW

2. Name of Operator

DEVON ENERGY CORPORATION (NEVADA)

3. Address and Telephone No.

20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405)552-4527

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL & 660' FWL, Sec. 29-17S-31E

5. Lease Designation and Serial No.

LC-029395-B

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Turner "B" #52

9. API Well No.

30-015-05442

10. Field and Pool, or Exploratory Area

Grayburg Jackson

11. County or Parish, State

Eddy County, NM

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other _____
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☒ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The following work was done to convert to water injection well:

1/14/97 to 1/17/97 - Cleaned out to 3450'.

1/18/97 - Perf'd 2998'-3420' (17 - .49" holes). Acidized Premier & Vacuum perfs 3269'-3420' w/3000 gals 15% HCl acid + 4000# rock salt. Acidized Grayburg perfs 2998'-3195' w/2150 gals 15% HCl acid.

1/19/97 - RIH w/5 1/2" AD-1 nickel plated pkr & 93 jts 2 3/8" IPC tbg. Set pkr @ 2912.57'. Tested to 320 psi for 15 min, held.

5/28/97 - Began injecting.

Post FD-3
6-27-97
prod to WIW

(ORIG. SGD.) DAVID R. GLASS

14. I hereby certify that the foregoing is true and correct

Signed

Karen Byers

Title

**KAREN BYERS DLM
ENGINEERING TECHNICIAN**

Date **05/29/97**

Approved by

Conditions of approval, if any:

Title

Date

SR