

APPROVED
JAN 29 1962
RONNIE E. SHOOK
ACTING DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces
Lease No. 00935(b)
Unit Turner T² 2D

RECEIVED

JAN 30 1962

SUNDRY NOTICES AND REPORTS ON WELLS

D. C. C.

ARTEGIA, OFFICE

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	X
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	Report of Perforation & Sand-	X
	oil Free	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

January 22, 1962

Well No. 62 is located 1900 ft. from SM line and 1900 ft. from E line of sec. 29

SE/4 Sec 29 17N 12E 107W
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Gregory Jackson Edley New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Moved in DEU (DARS). Jet perforated Premier Zone 3506-3516 w/20 1/2" holes. Set Retractable Bridge Plug at 3575'. Ran 2-1/2" CD tubing to 3520. Sandoil free treated parts 3506-36 w/15,000 gals jelled lss crude & 15,000 lbs sand preceded by 250 gals mud acid. Max Press 3000#, Min Press 1600#, inj rate 25 BPM. In 10 min SIP 1000#. Stopped & kicked well off. On 2 Potential test ending 6:00 AM 1-16-62, well flowed 150 bbls new 35.0 gravity oil & no water in 17 hours on 1/4" choke. The 7,000 100#, for a 24 hour calculated potential of 220 bbls oil. COR 620 to 1. Resampled thru new perforations 3506-3516.

RECEIVED

JAN 26 1962

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Sinclair Oil & Gas Company

Address 520 E Broadway

Hobbs, New Mexico

By [Signature]

Title Asst Dist Engt

Originals: USGS; es:WFD, JM, File