

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYN. M. O. C. C. COPY  
SUBMIT IN TRIPL  
(Other instructions  
verse side)TE\*  
re-Form approved.  
Budget Bureau No. 42-R1424.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER Plug & Abandon		5. LEASE DESIGNATION AND SERIAL NO. LC 029395 (b)	
2. NAME OF OPERATOR Atlantic Richfield Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR P. O. Box 1710, Hobbs, New Mexico 88240		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface  1980' FSL & 1755' FWL (Unit letter K)		8. FARM OR LEASE NAME Turner "B" (A)	
14. PERMIT NO.		9. WELL NO. 57	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3607' GR		10. FIELD AND POOL, OR WILDCAT Grayburg Jackson OGSA	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 30-17S-31E	
		12. COUNTY OR PARISH Eddy	
		13. STATE N.M.	

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Plug &amp; Abandon

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

On 4/10/75 rigged up & removed gate valve. Installed BOP. Ran 6-1/8" bit, washed dn from 1420-3490' to condition mud. POH w/bit. RIH w/tbg & pumped 100 sx cmt w/4% gel, 1/4# Flocele & 10# sd/sk. WOC. Check top of cmt @ 3120'. Cmt from 3490-3120'. Spotted 40 sx Cl C cmt w/LC material 2490-2630'. Spotted 40 sx Cl C cmt 1460-1600'. Spotted 20 sx gel, 8 sx cotton seed hulls, followed by 40 sx Cl C cmt w/4% gel, 1/4# Flocele flakes & 10# sd/sk. 1460-1600'. Spotted 4 sx Cl C cmt w/additives across 10-3/4" csg shoe @ 691'. POH w/tbg. Spotted 10 sx Cl C cmt plug @ surface. Installed regulation dry hole marker. Cleaned & levelled location. P&A effective 4/16/75. Final Report.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Dist. Drlg. Supv.

DATE 4/18/75

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side