Drawer DD

Form Approved. Budget Bureau No. 42-R1424

UNITED STATES Artesia, NM 88210

2000000	J. LEAGE	
OF THE INTERIOR	LC-029395	(b

DEPARTMENT OF THE INTERIOR	LC-029395 (b)	
C/SF GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR T	RIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME	RECEIVE
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME	APR 1 6 19
1. oil gas	Turner "B"	· · · · · · · · · · · · · · · · · · ·
well well other WIW	9. WELL NO.	O. C. D.
2. NAME OF OPERATOR ARCO Oil and Gas Company	76	ARTESIA, OFFIC
DIV OF ACTABLEC RECIFIED CO.	10. FIELD OR WILDCAT NAME	
3. ADDRESS OF OPERATOR	Grayburg Jackson S	
P. O. Box 1710-Hobbs, N M 88241-1710	11. SEC., T., R., M., OR BLK. A AREA	AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	30-17S-31E	
below.)	12. COUNTY OR PARISH 13.	STATE
AT SURFACE: 660' FSL & 660' FEL AT TOP PROD. INTERVAL:		N M
AT TOTAL DEPTH:	Eddy 14. API NO.	1\ 11
as above 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	24. /11 110.	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF,	KDB, AND WD)
	3656' GR	,
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:		
TEST WATER SHUT-OFF		
FRACTURE TREAT		
SHOOT OR ACIDIZE	(NOTE: Report results of multiple	completion or zone
PULL OR ALTER CASING	change on Form 9-330)	
MULTIPLE COMPLETE	- 10038 G/SAV/	
CHANGE ZONES	MZ	
ABANDON* X L	APR 14 1982	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statingly including estimated date of starting any proposed work. If well is a measured and true vertical depths for all markers and zones pertine	directionally drilled, give subsumant to this width? *CFOLOSEALS	CEVEY
	CHASNUELL PRICERY AGE	исо
Propose to plug & abandon in the following manu	iei.	
 Rig up, install BOP, POH w/CA. Push CIBP @ 3470' to 3570' PBD. 		
2 22521		
6 0/06 0/071	n top of retr. Circ b	ole w/9.5#
heavy gel mud.		•
5. Spot cmt plug @ $\pm 1500^{\circ}$. 6. Perf $4\frac{1}{2}$ '' csg @ $\pm 540^{\circ}$, break circ to surf.		
0. 1611 42 Cag c 1540 , break care to barr		•

7. Set cmt retr @ ± 500 ', circ cmt to surf. Close BH & sqz w/ ± 100 sx cmt.

8. Fill $4\frac{1}{2}$ " csg f/500' to surf, cut off WH, install regulation P&A marker, clean & level location for abandonment.

Subsurface Safety Valve: Manu. and Type		Set @ Ft.
18. I hereby certify that the foregoing is t	TITLE Dist. Drlg. S	upt. DATE 4/12/82
	(This space for Federal or State offi	ce use)
APPROVED BY	TITLE	PA APPROVED AS AMENDED

*See Instructions on Reverse Side