



# LOG OF OIL OR GAS WELL

LOCATE WELL CORRECTLY

Company Wilmar Oil Company Address Artesia, New Mexico  
Lessor or Tract Ginsberg Lease Field Loco Hills State New Mexico  
Well No. 3-A Sec. 8 T. 18 R. 31 Meridian N.M.P.M. County Eddy  
Location 660 ft. (N.) of S. Line and 1980 ft. (W.) of E. Line of Sec. 8 Elevation \_\_\_\_\_  
(Derrick floor relative to sea level)

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Signed [Signature]  
Title Secretary

Date Sept. 28, 1940

The summary on this page is for the condition of the well at above date.

Commenced drilling July 26, 1940 Finished drilling September 10, 1940

## OIL OR GAS SANDS OR ZONES

(Denote gas by G)

No. 1, from 3102 to 3155 No. 4, from \_\_\_\_\_ to \_\_\_\_\_  
No. 2, from \_\_\_\_\_ to \_\_\_\_\_ No. 5, from \_\_\_\_\_ to \_\_\_\_\_  
No. 3, from \_\_\_\_\_ to \_\_\_\_\_ No. 6, from \_\_\_\_\_ to \_\_\_\_\_

## IMPORTANT WATER SANDS

No. 1, from 650 to 660 No. 3, from \_\_\_\_\_ to \_\_\_\_\_  
No. 2, from \_\_\_\_\_ to \_\_\_\_\_ No. 4, from \_\_\_\_\_ to \_\_\_\_\_

## CASING RECORD

Size casing	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Cut and pulled from	Perforated		Purpose
							From—	To—	
<u>8 1/2"</u>	<u>32</u>	<u>10</u>	<u>J&amp;L</u>	<u>728</u>	<u>Texas</u>				

## HISTORY OF OIL OR GAS WELL

## MUDDING AND CEMENTING RECORD

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
<u>8 1/2"</u>	<u>728</u>	<u>50</u>	<u>Halliburton</u>		
<u>7"</u>	<u>3000</u>	<u>100</u>	<u>Halliburton</u>		<u>100 sacks heavy mud run ahead of cement</u>

## PLUGS AND ADAPTERS

Heaving plug—Material \_\_\_\_\_ Length \_\_\_\_\_ Depth set \_\_\_\_\_  
Adapters—Material \_\_\_\_\_ Size \_\_\_\_\_

## SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out
<u>4"</u>	<u>6</u>	<u>Nitroglycerin</u>	<u>140 qts</u>	<u>9-10-40</u>	<u>3115-3160</u>	<u>to 3160</u>

## TOOLS USED

Rotary tools were used from \_\_\_\_\_ feet to \_\_\_\_\_ feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet  
Cable tools were used from 0 feet to 3160 feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet

## DATES

Sept. 25, 1940 Put to producing September 20, 1940

The production for the first 24 hours was 200 barrels of fluid of which 100 % was oil; \_\_\_\_\_ %

FOLD MARK