



## 

1  $\frac{1}{2}$ ۲

per d ٠. 1.

ł

. .

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

۰,

Т. м. т. м. 1

1

### WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

Budco 011 & Ga	s Company	art	esia, New	Mexico	
1 'SDDDMUM (	17 LITHIFALOF				•
V.H.McNutt-State	Well No	in SW of Se	e. 21	, T{	3
Lease R. <u>28</u> , N. M. P.					County.
Well isfeet south	of the North line and	feet west of the	East line of		·······
If State land the oil and gas l	ease is No	Assignment No	t,t,		
If patented land the owner is_		, A	ddress		
If Government land the perm	aittee is	, A	ddress		
The Lessee is		, A	ddress		
Drilling commenced M	lay 5 19	25 Drilling was com	pletedJun	ie 18	25
Name of drilling contractor_	Paton Brothe	rs, Address	Artesia,	New Me	xico
Elevation above sea level at					
The information given is to b					
The information given is to b		ANDS OR ZONES			
No. 1, from 2005				to	
No. 2, from					
No. 3, from	to	No. 6, from		_to	
	IMPORT	ANT WATER SANDS			
Include data on rate of wate	er inflow and elevation t	o which water rose in ho	le.		
No. 1, from 254	to	260	feet		
No. 2, from			feet		
No. 3, from	to		feet		
			feet		
No. 4, from					

#### CASING RECORD

	A- 0114	THREADS			KIND OF SHOE	D OF CUT & FILLED OE FROM	PERFORATED		PURPOSE
SIZE	WÉIGHT PER FOOT	PER INCH	MAKE	AMOUNT			FROM	то	
12 <u>1</u> "	50#	10	Y.T.	2301	Tex ty	pe			
10"	40#	10	Y.T.	355	Tex ty	ne			
82"	32#	10	Υ.Τ.	680		pe			

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
-						
_						

						<u></u>	
		P	LUGS AND AD		Depth Se	t	
Adapters—	-Material						
		RECORD OF SHO				¥	
SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEAN	ED OUT
			60 qts	6-10-25	2005-519	2195	
					<u> </u>	<u>, <u>k</u> <u> </u></u>	
Results of	shooting or che	mical treatment	······································				
		RECORD OF	DRILL-STEM	AND SPRCIAL	TESTS		
If drill-st	em or other spec	ial tests or deviation				e sheet and attach	1 hereto.
II UIIII SU			TOOLS U				
Potery to	ola were used f	romfee			rom	feet to	feet
Cable to	ols were used f	romfee	t to <u>2193</u>	feet, and f	rom	_feet to	feet
			PRODUCT				
		- <u> </u>					
-	uction of the first	24 hours was 60	bbls ba	rrels of fluid o	f which		
emulsion	;%	water; and	% sedime	ent. Gravity,	Be0		
		hours		allons gasoline	per 1,000 cu. ft.	of gas	
Rock pre	ssure, lbs. per sq	. in					
			EMPLOY				D-111-
<u></u>	,,,,,,						
			, Driller				., Drille
			TION RECORD				
		that the information			te and correct r	ecord of the wel	l and al
work do	ne on it so far a	s can be determined :	from available	records.			
		hotore me this	4th				

Subscribed and sworn to before me this	Place Date
August 19 37	Name O. L. McCukheon
SEAL	Position Field Supt.
Stephen W. Gilbert Notary Public	Representing Rodco Oil & Ref. Corp.
My Commission expires March 5th, 1941	Company or Operator Artesia, New Mexico
-	Auur (53)

# FORMATION RECORD

FROM	то	THICKNESS IN FEET	FORMATION
$\begin{array}{c} 0\\ 15\\ 70\\ 125\\ 260\\ 375\\ 450\\ 650\\ 810\\ 855\\ 1790\\ 1808\\ 1885\\ 1925\\ 2005\\ 2019\\ 2148\\ 2150\\ 2222 \end{array}$	15 70 125 260 375 450 650 810 855 1790 1808 1885 1925 2005 2019 2148 2150 2222	•	Gyp Red sand Sandy shale Sand, 250-260 water sand Gyp rock Red sand White lime Gyp Red rock Lime White sand, hard Lime Red sand Lime Cil sand Sandy'lime Blue shale Lime Total depth
	ξ		

