

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>MORRIS R. ANTWEIL</u> <u>J. DON HUGGINS, INC.</u>		Lease <u>CATHERINE WILLIAMS</u>		Well # <u>I</u>	
Location of Well	Unit <u>0</u>	Section <u>9</u>	Township <u>18 S</u>	Range <u>23 E</u>	County <u>EDDY</u>
Drilling Contractor <u>Cactus Drilling Co.</u>	Type of Equipment <u>ROTARY</u>				

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2"</u>	<u>13 3/8"</u>	<u>48 #</u>	<u>USED</u>	<u>120'</u>	<u>CIRC.</u>
<u>12 1/4"</u>	<u>8 5/8"</u>	<u>24 #</u>	<u>new</u>	<u>1800'</u>	<u>CIRC.</u>
<u>7 7/8"</u>	<u>5 1/2"</u>	<u>14-15.5-17 #</u>	<u>new</u>	<u>8500'</u>	<u>2.50</u>

Casing Data:

Surface 44 joints of 8 5/8 inch 24 # Grade Line pipe threaded + collared
mostly long joints 50' ± (Approved) (Rejected) used pipe - good appearance
Inspected by LOBLEY date 5-11-63

Cementing Program

Size of hole 11 Size of Casing 8 5/8 Sacks cement required 576 sacks = 100% EXCESS

Type of Shoe used GUIDE Float collar used YES Btm 3 jts welded THRED-LOK

TD of hole 1801 GL. Set 1801 Feet of 8 5/8 inch 24 # Grade

New used csg. @ 1801 with 50 sacks neat cement around shoe

+ 526 sax 50-50 POZ additives 270 GEL, 270 CASH, + 25 # GILSONITE PER SK.

Plug down @ 10:35 (AM) (PM) Date 5-13-63

Cement circulated YES No. of Sacks 200 sax.

Cemented by HALLIBURTON Witnessed by LOBLEY

Temp. Survey ran @ (AM) (PM) Date (AM) top cement @ (AM)

Casing test @ (AM) (PM) Date (AM)

Method Used (AM) Witnessed by (AM)

Checked for shut off @ 2:20 (AM) (PM) Date 5-14-63

Method used Drilled up Hole Witnessed by LOBLEY OK.

Remarks: 4 Centralizers lower 120' - 2 Baskets 500' + 630'

Plugging July 28 3, 1963

25 sax at TD, 20 sax at 6000, 20 sax across pipe st. 6 1800

20 sax at 600 last plug down at 7:50 AM July 3.

Witnessed by

AP P. H. B.