

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division
811 S. 1st Street
Artesia, NM 88210-2834

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other WIW

2. Name of Operator

SDX Resources, Inc.

3. Address and Telephone No.

PO Box 5061, Midland, TX 79704 915/685-1761

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL 1980' FEL
Unit G, Sec 11, T18S, R28E

5. Lease Designation and Serial No.

NM-54184

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Dunn B Federal #29

9. API Well No.

30-015-10117

10. Field and Pool, or Exploratory Area

Artesia QN-GB-SA

11. County or Parish, State

Eddy Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

P&A Proposal:

Set CIBP @ 2450' & cap w/20 sx. TOC @ 2160'

Cut 4-1/2" csg @ appx 1700' & pull

Spot 30 sx plug from 1700 - 1600' - Tag

Spot 30 sx plug @ 700'

Spot 30 sx plug from 450 - 350' - Tag

Spot 10 sx surface plug

Install marker

14. I hereby certify that the foregoing is true and correct

Signed

David R. Glass

Title Engineer

Date 02/10/00

(This space for Federal or State office use)

(ORIG. SGD.) DAVID R. GLASS

Title

PETROLEUM ENGINEER

Date

FEB 16 2000

Approved by

Conditions of approval, if any:

SEE ATTACHED FOR

CONDITIONS OF APPROVAL

Title 18 U.S.C. 1001 (a)(1) and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See instruction on Reverse Side

RECEIVED
FEB 14 1952

RECEIVED
FEB 14 1952

RECEIVED
FEB 14 1952

Dunn B # 29
1980' FNL & 1980 FEL
Sec. 11 T18S R28E
Edy Co., N.M.

Existing Condition:

10" hole to 408' with 408' of 8-5/8" csg cemented with 75 sxs. (TOC calculated at surface.)

8' to 2486' - 6" to 2654' with 2654' of 4-1/2" casing cemented with 175 sxs. (TOC=1736 ' by calculation)

Perfs: 2526'-2579.

2-3/8" PC tubing with AD-1 at 2447'.

Formation Tops:	Top Salt	505'
	Base Salt	670'
	Queen:	1845'
	Grayburg:	2220'
	San Andres:	2584'

P&A Proposal:

- 1.) Set CIBP at 2450' and cap with 20 sxs. TOC at 2160
- 2.) Cut 4-1/2" casing at ~1700' and pull.
- 3.) Spot 30 sx. Plug from 1700-1600'.
- 4.) Spot 30 sx plug at 700'
- 5.) Spot 30 sx plug from 450-350
- 6.) Spot 10 sx surface plug.
- 7.) Install marker.

RECEIVED
JOURNAL OF THE
NATIONAL ACADEMY OF SCIENCES

2000 FEB 14 A 9:52

RECEIVED