

Form 9-331a
(Feb. 1961)

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYBudget Bureau No. 42-R358.4.
Form Approved.Land Office Artesia, N. M.Lease No. NM 0318474Unit 7

RECEIVED

SEP 30 1963

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

23 September

1963

Well No. 1 is located 990 ft. from N line and 2310 ft. from E line of sec. 29SE/4 of SW/4
(1/4 Sec. and Sec. No.)13-S
(Twp.)30-E
(Range)NMPM
(Meridian)N. Benson (Queen-
Crayburg)
(Field)Eddy
(County or Subdivision)New Mexico
(State or Territory)The elevation of the derrick floor above sea level is 3443 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

See attached detail sheet

RECEIVED
SEP 25 1963
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Floyd W. Smith & Company, Inc.Address Box 1515Midland, TexasBy Kevin E. Hildebrand
Title Asst. General Mgr.

#1 USA - Holt

Spudded 8 3/4" hole at 4:00 pm 8-28-63

Drilled 8 3/4" hole to 565' and ran 549' 7" 23# 10V thread
csg. set at 551' and cemented w/140 sx inoor cement w/
3% CaCl. Cement circ.

Drilled 6 3/4" hole to a TD of 3225'

Ran Gamma Ray-Sonic log

Ran 3170' 4 1/2" 9.5# J-55 csg. set at 3170' and cemented
w/85 sx inoor w/50:50 poamix w/4% gel and 46 sx neat cement

Ran GR-N Tie in log and perforated 4 1/2" csg. w/2 3/8" JHPF
a at 3026, 3032, 3075, 3079, & 3141

Spotted 250 gal 15% NE acid, bk dn form and frac treated w/30,000
gal Refined oil w/ 1 1/2# sand per gal

Perf. 4 1/2" csg. w/2 1/2" JHPF @ 2829, 2842, 2880, 2944, &
2948

Set Howco Retubi Bridge Plug at 2980'

Spotted 250 gal 15% NE acid, bk dn form and treated w/30,000
gal Refined oil w/ 1 1/2 PSPO. 1342 BOLTR

RECEIVED
SEP 15 1963
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO