(SUBMIT IN TRIPLICATE) UNITED STATES

DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

/<	,
	RECEIVED SEP
	CEIN
	SEP , ED
LS	SEP 30 19LJ

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF ARTESIA DE IC
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING.
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING.	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL.	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Leo R. Manning Fed. "B"

September 23 1963 Hobbs, New Mexico

Well No. 7 is located 1980 ft. from $\binom{N}{S}$ line and 1980 ft. from $\binom{N}{W}$ line of sec. 28

NE/4 of SW/4 Sec. 28 (1/4 Sec. and Sec. No.)

Queen Gravburg

(Meridian)

North Benson

Eddy (County or Subdivision)

The elevation of the derrick floor above sea level is 3378. ft.

DETAILS OF WORK

bjective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement-ing points, and all other important proposed work)

TD - 3350'

544' of 7" OD casing (14.0 lb - Spiral Weld) set at 556'.

Ran 3339' of 4-1/2" OD casing (9.5 lb - J-55) and set at 3350'. Cement with 350 sacks of Class "C" with 10% salt. Plug at 3326'. Job complete 7:45 P.M. 9-21-63.

Tested 4-1/2" OD casing for 30 minutes with 1000 psi from 5:00 to 5:30 P.M. 9-22-63. Tested O.K. Drilled plug and retested from 6:30 to 7:00 P.M. 9-22-63. Tested O.K. Job complete 7:00 P.M. 9-22-63.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commen Company TEXACO Inc. Address P. O. Drawer 728

Hobbs, New Mexico