Form Approved. Budget Bureau No. 42-R1424

## UNITED STATES

UNITED STATES	5. LEASE 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5
DEPARTMENT OF THE INTERIOR	NM-033775
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different	North Benson Oueen Unit
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas	North Benson Queen Unit
well well other	9. WELL NO.
TEXACO Inc.	10. FIELD OR WILDCAT NAME
	Benson Queen Grayburg North
P.O. Box 728 - Hobbs, New Mexico 88240	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY See space 17	AREA
below.) AT SURFACE: 1743' FNL & 784' FNL	Sec. 28, T-18-S, R-30-E
AT TOP PROD. INTERVAL: Unit Letter 'E I	Eddy Lea New Mexico
AT TOTAL DEPTH:	14. AP NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	
REFORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)   3510   (DF)     日本
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	<u> </u>
TEST WATER SHUT-OFF   FRACTURE TREAT	
FRACTURE TREAT	그는 그를 하는 그를 고향하다.
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING  MULTIPLE COMPLETE  MULTIPLE COMPLETE	change on Form 9-330.) 가 다 를 보실 한국 기계
CHANGE ZONES	
ABANDON*	
(other) To Keputi Casting Leak	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is di measured and true vertical depths for all markers and zones pertinent	rectionally drilled, give subsurface locations and
1. Rig up. Pull rods & pump. Install BOP. Pul	l tubing.
2. Set RBP @ 2500' & dump 20' sand on plug.	្រុស្ស៊ី ខេត្ត ស្រុសស៊ីម៉ូន (Constitution of the Constitution of the Constitution of the Constitution of the Co
3. Establish circulation in 7" - 4-1/2" casing a	annulus.
4. Squeeze 4-1/2" csg leak @ approx. 600' w/350 2% CaCl. Circulate cement. WOC.	sx. Class C cement containing
5. Pressure test 4-1/2" casing to 1000# for 30 r	minutes
6. Pull RBP. Install pumping equipment. Test 8	return to production.
	를 보고 있는 것이 되었다. 그런 사람이 되었다. 이 기업을 하는 10년 1일 기업을 보고 있다.
	September 1997 And Control of the Septem
Subsurface Safety Valve: Manu. and Type	Sett@\F!-
18. I hereby certify had the for going is true and correct	
SIGNED SILLUM TITLE ASST. Dist. SI	1Dt. DATE 5A77-79
SIGNED TILE MOSC. DISC. SC	APO DATE OFWITZUM,

(This space for Federal or State office use)

ACTING DISTRICT ENGINEER

APPROVED BY THE SALA CONDITIONS OF APPROVAL, IF ANY: